

NACOMATIC

Effective: 08-April-2010

Expires: 06-May-2010

Your Ad Here

~ 100,000 Page views/month

Contact:

Doug Ranz

248-318-0011

NACOMATIC@hotmail.com

Warranty

I make absolutely no warranty nor guarantee whatsoever about the accuracy, availability, applicability and/or correctness of any of the information in this document.

The official, original NACO documents are available for your downloading pleasure from: <http://naco.faa.gov/index.asp?xml=naco/onlineproducts>

Copyright

This compilation is protected by US copyright laws and international copyright treaties.

Limitations

The sale, hosting and/or distribution of this document in any and all forms, is prohibited.

Release from Liability

All users of this compilation must agree to be legally bound hereby, that Douglas R. Ranz ("Released Party") SHALL NOT BE LIABLE FOR MY DEATH OR INJURY TO MY PERSON, OR FOR ANY LOSS FOR DAMAGE TO MY PROPERTY OR REPUTATION caused in any manner whatsoever, whether attributable to the negligence of the Released Party, or for any other reason, occurring during the time that I am operating an aircraft.

I do hereby waive any right of action against the Released Party from any and all causes or claims that I may have against them from the beginning of time. I further agree not to sue on any such cause or claim. This agreement shall not release liability for gross negligence or willful misconduct of the Released Party. I agree to indemnify and hold the Released Party harmless for any losses, judgments, damages or fees he may incur, including but not limited to attorneys fees, arising out any lawsuit related to the planning, flight and/or enforcement of or legal challenge to this agreement. It is my intention that this agreement be interpreted and enforced to the maximum extent allowed by Michigan law.

HI Min Alt	-	5
HI Min TO	-	8
HNL	-	23
HNM	-	12
ITO	-	14
JRF	-	84
KOA	-	67
LIH	-	96
LNK	-	92
MKK	-	87
MUE	-	80
OGG	-	52

HI Mins - Alternates	-	5
HI Mins - Take-Off	-	8
HANA	HNM	- 12
HILO	ITO	- 14
HONOLULU	HNL	- 23
KAHULUI	OGG	- 52
KAILUA-KONA	KOA	- 67
KAMUELA	MUE	- 80
KAPOLEI	JRF	- 84
KAUNAKAKAI	MKK	- 87
LANAI CITY	LNK	- 92
LIHUE	LIH	- 96



INSTRUMENT APPROACH PROCEDURE CHARTS

A IFR ALTERNATE AIRPORT MINIMUMS

Standard alternate minimums for non precision approaches are 800-2 (NDB, VOR, LOC, TACAN, LDA, VORTAC, VOR/DME, ASR or WAAS LNAV); for precision approaches 600-2 (ILS or PAR). Airports within this geographical area that require alternate minimums other than standard or alternate minimums with restrictions are listed below. NA - means alternate minimums are not authorized due to unmonitored facility or absence of weather reporting service. Civil pilots see FAR 91. IFR Alternate Minimums: Ceiling and Visibility Minimums not applicable to USA/USN/USAF. Pilots must review the IFR Alternate Minimums Notes for alternate airfield suitability.

NAME ALTERNATE MINIMUMS

BABELTHUAP, KOROR, PS

BABELTHUAP/KOROR **NDB Rwy 9¹**
RNAV (GPS) Rwy 9
RNAV (GPS) Rwy 27

NA except standard for operators with approved weather reporting service.

¹Categories A,B, 900-2; Category C, 900-2½; Category D, 900-2½.

DALAP, RM

MARSHALL ISLANDS INTL **NDB Rwy 7¹**
NDB Rwy 25¹
RNAV (GPS) Rwy 7²
RNAV (GPS) Rwy 25²

¹NA when Majuro Radio closed.

²NA when local weather not available.

GUAM, GQ

GUAM INTL **ILS or LOC Rwy 6L¹**
ILS or LOC Rwy 6R¹
RNAV (GPS) Y Rwy 6R²
RNAV (GPS) Y Rwy 24L³
RNAV (GPS) Y Rwy 24R³
TACAN Rwy 24R⁴

¹ILS, LOC, Categories A,B, 1200-2; Categories C,D, 1200-3.

²Category D, 800-2½.

³Category C, 800-2½; Category D, 800-2½.

⁴Categories A, B, 900-2; Category C, 900-2½; Category D, 900-3.

HILO, HI

HILO INTL **ILS or LOC Rwy 26**
 ILS, Category D, 700-2.
 NA when control tower closed.

NAME ALTERNATE MINIMUMS

HONOLULU, HI

HONOLULU INTL **ILS Rwy 4R¹**
LDA/DME Rwy 26L¹
RNAV (GPS) Y Rwy 4R²
RNAV (GPS) Y Rwy 8L³
VOR/DME or TACAN or GPS-B⁴
VOR or TACAN or GPS-A¹
VOR or TACAN Rwy 4R⁵

¹Category E, 1500-3.

²Category D, 900-2½; Category E, 1500-3.

³Category D, 900-2½; Category E, 1700-3.

⁴Category E, 900-3.

⁵Category D, 800-2½.

KAHULUI, HI

KAHULUI **ILS Rwy 2¹²**
LOC/DME BC Rwy 20²
NDB/DME Rwy 2²
RNAV (GPS) Rwy 23³
VOR/DME or TACAN Rwy 20⁴

¹ILS, Category E, 1200-3. LOC, Category E, 1200-3.

²NA when control tower closed.

³NA when local weather not available.

⁴NA when control tower closed, except for operators with approved weather reporting service.

KAILUA-KONA, HI

KONA INTL AT KEAHOLE **LOC Rwy 17**
 NA when control tower closed.

KAMUELA, HI

WAIMEA-KOHALA **VOR/DME-A**
VOR/DME Rwy 4¹

Categories A,B, 1100-2, Category C, 1100-3, Category D, 1300-3.

¹Categories A,B, 900-2, Category C, 900-2½, Category D, 1300-3.



ALTERNATE MINS



NAME ALTERNATE MINIMUMS
KAPOLEI, HI
 KALAELOA (JOHN RODGERS **NDB Rwy 4R**
 FIELD)
 Category C, 800-2¼; Category D, 800-2½.

KAUNAKAKAI, HI
 MOLOKAI **VOR or TACAN or GPS-A**
 Categories A,B, 1200-2; Categories C,D,
 1200-3.

KOSRAE, FM
 KOSRAE **NDB/DME-A¹²**
RNAV (GPS) Rwy 5³
RNAV (GPS) Rwy 23⁴

¹NA when NDB (UKS) not monitored or local weather not available. Both NDB (UKS) monitored and local weather available Monday through Saturday from 2100 UTC to 0500 UTC (0800 local to 1600 local).

²800-3.

³NA except standard for operators with approved weather reporting service.

⁴NA except categories A,B, standard, Category C, 800-2¼, Category D 800-2½, for operators with approved weather reporting service.

LANAI CITY, HI
 LANAI **ILS or LOC Rwy 3**
VOR or TACAN or GPS-A
VOR or TACAN or GPS Rwy 3

NA when local weather not received except for operators with approved weather reporting service.

LIHUE, HI
 LIHUE **ILS or LOC Rwy 35¹**
RNAV (GPS) Rwy 17²
RNAV (GPS) Y Rwy 21²
RNAV (GPS) Y Rwy 35³

¹ILS,LOC,NA when control tower closed; LOC,Category E, NA.

²Category B, 900-2; Category C, 1000-2¼; Category D, 1000-3.

³Category C, 800-2¼; Category D, 800-2½.

MIDWAY ATOLL, MQ
 HENDERSON FIELD **NDB Rwy 6**
NDB Rwy 24
RNAV (GPS) Rwy 6
RNAV (GPS) Rwy 24

NA except standard for operators with approved weather reporting service.

NAME ALTERNATE MINIMUMS
POHNPEI ISLAND, FM
 POHNPEI INTL **NDB or GPS-B¹**
NDB or GPS-C¹
NDB/DME or GPS-A¹
NDB/DME Rwy 9, 800-3
RNAV (GPS) Rwy 9²
RNAV (GPS) Rwy 27¹

NA when local weather not available.

¹Category D, 800-2¼.

²Categories A,B, 1000-2¼; Category C, 1000-2¼; Category D, 1000-3.

SAIPAN, CQ
 FRANCISCO C. ADA/
 SAIPAN INTL **GPS Rwy 7**
GPS Rwy 25

NA except standard for operators with approved weather reporting service.

ROTA INTL **GPS Rwy 9¹**
GPS Rwy 27¹
NDB Rwy 9²³
NDB Rwy 27²³

¹NA except standard for operators with approved weather reporting service.

²NA when terminal weather not available 0900 UTC to 2000 UTC except for operators with approved weather reporting service. Terminal weather available on Rota Radio 123.6 from 2000 UTC to 0900 UTC.

³Category D, 800-2¼.

TINIAN ISLAND, CQ
 TINIAN INTL **NDB-A**
 Category C, 800-2¼; Category D, 800-2½.
 NA when local weather not available except for operators with approved weather reporting service.

TUTUILA, AQ
 PAGO PAGO INTL **ILS/DME Rwy 5¹**
NDB-C²
VOR-D³⁴

¹ILS, Categories C,D, 700-2.

²Category D, 800-2¼.

³NA when control zone not in effect.

⁴Categories A,B, 1100-3; Categories C,D, 1100-3.



ALTERNATE MINS

E3



09071

NAME ALTERNATE MINIMUMS

WENO ISLAND, FM

CHUUK INTL **NDB/DME Rwy 4¹**
NDB or GPS-A¹
NDB or GPS-B¹
RNAV (GPS) Rwy 4²

¹800-3.

²NA except standard for operators with approved weather reporting service.

YAP ISLAND, FM

YAP INTL **NDB Rwy 25¹**
NDB/DME Rwy 25²

¹Categories A,B, 900-2; Category C, 900-2¾; Category D, 900-3.

²Categories A,B, 900-2; Category C, 900-2½; Category D, 900-2¾ .

INSTRUMENT APPROACH PROCEDURE CHARTS

IFR TAKE-OFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

Civil Airports and Selected Military Airports

ALL USERS: Airports that have Departure Procedures (DPs) designed specifically to assist pilots in avoiding obstacles during the climb to the minimum enroute altitude, and/or airports that have civil IFR take-off minimums other than standard, are listed below. Take-off Minimums and Departure Procedures apply to all runways unless otherwise specified. Altitudes, unless otherwise indicated, are minimum altitudes in MSL.

DPs specifically designed for obstacle avoidance are referred to as Obstacle Departure Procedures (ODPs) and are described below in text, or published separately as a graphic procedure. If the (Obstacle) DP is published as a graphic procedure, its name will be listed below, and it can be found in either this volume (civil), or a separate Departure Procedure volume (military), as appropriate. Users will recognize graphic obstacle DPs by the term "(OBSTACLE)" included in the procedure title; e.g., TETON TWO (OBSTACLE). If not assigned a SID or radar vector by ATC, an ODP may be flown without ATC clearance to ensure obstacle clearance.

Graphic DPs designed by ATC to standardize traffic flows, ensure aircraft separation and enhance capacity are referred to as "Standard Instrument Departures (SIDs)". SIDs also provide obstacle clearance and are published under the appropriate airport section. ATC clearance must be received prior to flying a SID.

CIVIL USERS NOTE: Title 14 Code of Federal Regulations Part 91 prescribes standard take-off rules and establishes take-off minimums for certain operators as follows: (1) Aircraft having two engines or less - one statute mile. (2) Aircraft having more than two engines - one-half statute mile. These standard minima apply in the absence of any different minima listed below.

MILITARY USERS NOTE: Civil (nonstandard) take-off minima are published below. For military take-off minima, refer to appropriate service directives.

NAME TAKE-OFF MINIMUMS

BABELTHUAP, KOROR, PS

BABELTHUAP/KOROR (ROR)

AMDT 1 09015 (FAA)

TAKE-OFF MINIMUMS: **Rwy 27**, 400-1 or std. with a min. climb of 296' per NM to 500.DEPARTURE PROCEDURE: **Rwy 9**, climb runway heading to 700 then as cleared.**DALAP, RM**

MARSHALL ISLANDS INTL (MAJ)

ORIG 10098 (FAA)

NOTE: **Rwy 7**, antenna on building 215' from DER, 446' left of centerline, 48' AGL/54' MSL. Obstruction light on AMOM 44' from DER, 269' left of centerline, 33' AGL/39' MSL. Obstruction light on WSK 10' from DER, 245' right of centerline, 23' AGL/29' MSL. Tree 934' from DER, 243' left of centerline, 39' AGL/45' MSL. Bush 555' from DER, 187' right of centerline, 17' AGL/23' MSL.**Rwy 25**, obstruction light on WSK 11' from DER, 246' left of centerline, 23' AGL/29' MSL. Post 51' from DER, 252' right of centerline, 8' AGL/14' MSL. Tree 996' from DER, 39' left of centerline, 31' AGL/37' MSL. Tree 563' from DER, 5' right of centerline, 20' AGL/26' MSL. Bushes beginning 207' from DER, from 124' left to 207' right of centerline, up to 14' AGL/20' MSL. Vehicle on roadway 130' from DER, 241' right of centerline, 15' AGL/20' MSL.

NAME TAKE-OFF MINIMUMS

GUAM, GQ

GUAM INTL (GUM)

ORIG -A 09071 (FAA)

TAKE-OFF MINIMUMS: **Rwys 6L, 6R**, 500-1 or std. with a min. climb 360' per NM to 800. **Rwys 24L, 24R**, 500-1 or std. with a min. climb of 300' per NM to 1400.DEPARTURE PROCEDURE: **Rwys 6L, 6R**, climb runway heading to 800 before turning. **Rwys 24L, 24R** climb runway heading to 1400 before turning.**HANA, HI**

HANA (HNM)

ORIG 05244 (FAA)

DEPARTURE PROCEDURE: Use LINDBERG DEPARTURE.

HILO, HI

HILO INTL (ITO)

AMDT 6 05356 (FAA)

DEPARTURE PROCEDURE: Use PARIS DEPARTURE.

HONOLULU, HI

HONOLULU INTL (HNL)

AMDT 7 85269 (FAA)

DEPARTURE PROCEDURE: use HONOLULU DEPARTURE.



KAHULUI, HI

KAHULUI (OGG)

AMDT 6 09015 (FAA)

TAKE-OFF MINIMUMS: **Rwy 23**, NA-ATC.DEPARTURE PROCEDURE: **Rwy 2**, climb on a heading between 310° CW to 053° from departure end of runway.**Rwy 5**, climb on a heading between 307° CW to 040° from departure end of runway. **Rwy 20**, climb on a heading of 185° from departure end of runway.NOTE: **Rwy 2**, bush/trees beginning 190' from departure end of runway, 362' left of centerline, up to 60' AGL/79' MSL. Pipe on building 339' from departure end of runway, 289' right of centerline, 20' AGL/25' MSL. Bush beginning 902' from departure end of runway, 637' right of centerline, up to 20' AGL/39' MSL. **Rwy 5**, trees 2359' from departure end of runway, 512' left of centerline, 56' AGL/75' MSL. Fence beginning 20' from departure end of runway, 299' right of centerline, up to 7' AGL/31' MSL. Bush/trees beginning 291' from departure end of runway, 300' right of centerline, up to 76' AGL/95' MSL. **Rwy 20**, bush 22' from departure end of runway, 236' right of centerline, 2' AGL/55' MSL. Bush/trees beginning 24' from departure end of runway, 173' left of centerline, up to 29' AGL/68' MSL.

KAILUA-KONA, HI

KONA INTL AT KEAHOLE

DEPARTURE PROCEDURE: **Rwy 17**, northwest-bound climb runway heading to 500 then climbing right turn to assigned route; eastbound climb runway heading to 500 then climbing right turn, heading 360°, to 2000, then climb via V3. **Rwy 35**, northwestbound climb runway heading to 500 then climbing left turn to assigned route; eastbound climb runway heading to 2000 then climb via V3.

KAMUELA, HI

WAIMEA-KOHALA (MUE)

AMDT 1 05076 (FAA)

TAKE-OFF MINIMUMS: **Rwy 4**, 400-2 or std. with a min. climb of 240' per NM to 3100.DEPARTURE PROCEDURE: **Rwy 4**, climb via heading 041° to 3100 then climbing right turn via heading 080° and MUE VOR/DME R-057 to 6000 to VELLA INT, then as assigned. **Rwy 22**, climb via heading 233° and MUE VOR/DME R-234 to 5000 to JASON INT, then as assigned.NOTE: **Rwy 4**, windsock 158' from departure end of runway, 299' right of centerline, 25' AGL/2702' MSL. Fence 2754' from departure end of runway, 323' right of centerline, 12' AGL/2741' MSL. Tree 5200' from departure end of runway, 179' right of centerline, 50' AGL/2817' MSL. Tree 5331' from departure end of runway, 110' left of centerline, 50' AGL/2829' MSL. Tree 1.3 NM from departure end of runway, 739' right of centerline, 50' AGL/2864' MSL. Tree 1.3 NM from departure end of runway, 1741' left of centerline, 50' AGL/2889' MSL. Antenna 1.8 NM from departure end of runway, 1094' left of centerline 152' AGL/2992' MSL. Rising terrain beginning 1.5 NM from departure end of runway, 3.9 NM left of centerline, up to 13796' MSL. **Rwy 22**, cactus at departure end of runway, 191' left of centerline, 10' AGL/2668' MSL. Tree at departure end of runway, 353' right of centerline, 50' AGL/2687' MSL. Bush 673' from departure end of runway, 186' left of centerline, 30' AGL/2673' MSL. Pole 1058' from departure end of runway, 124' left of centerline, 20' AGL/2683' MSL. Rapidly rising terrain beginning 1.5 NM from departure end of runway, 4209' left of centerline, up to 5513' MSL.

KAPOLEI, OAHU ISLAND, HI

KALAELOA (JOHN RODGERS FIELD) (JRF)

ORIG 09295 (FAA)

DEPARTURE PROCEDURE: DME Required. **Rwys 4L, 4R, 11**, climb heading 200° to intercept HNL VORTAC R-241 to GECKO/HNL 22.4 DME before proceeding on course. **Rwys 22L, 22R**, climb heading 224° to intercept HNL VORTAC R-241 to GECKO/HNL 22.4 DME before proceeding on course. **Rwy 29**, climb heading 210° to intercept HNL VORTAC R-241 to GECKO/HNL 22.4 DME before proceeding on course.NOTE: **Rwy 11**, tree 1533' from DER, 831' left of centerline, 60' AGL/70' MSL. **Rwy 22L**, vehicles on road 305' from DER, 195' left of centerline, 15' AGL/26' MSL. **Rwy 29**, tree 1794' from DER, 573' left of centerline, 60' AGL/99' MSL.

TAKE-OFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

KAUNAKAKAI, HI

MOLOKAI (MKK)

AMDT 5 05300 (FAA)

TAKE-OFF MINIMUMS: **Rwy 5**, std. with a min. climb of 395' per NM to 1600 or 1900-2½ for climb in visual conditions. **Rwy 23**, std. with a min. climb of 446' per NM to 1600 or 1900-2½ for climb in visual conditions. **Rwy 35**, 200-1 or std. with a min. climb of 441' per NM to 800.

DEPARTURE PROCEDURE: **Rwy 5**, climb via heading 040° to 1500 then climbing left turn direct MKK VORTAC, or climb in visual conditions to cross Molokai Airport southwestbound at or above 1800 via the MKK R-067 to MKK VORTAC, thence...

Rwy 17, climb via heading 169° to 1500 then climbing right turn direct MKK VORTAC, thence...

Rwy 23, climbing left turn via heading 170° to 1700 then climbing right turn direct MKK VORTAC or climb in visual conditions to cross Molokai Airport southwestbound at or above 1800 via the MKK R-067 to MKK VORTAC, thence...

Rwy 35, climb via heading 349° to 1500 then climbing left turn direct MKK VORTAC, thence...

...climb in MKK VORTAC holding pattern (hold NE, right turn, 236° inbound) to cross MKK at or above MCA/MEA for route of flight.

NOTE: **Rwy 5**, pole 2254' from departure end of runway, 222' right of centerline, 45' AGL/565' MSL, tree 1.12 NM from departure end of runway, 720' right of centerline, 50' AGL/675' MSL. Fenceline beginning 147' from departure end of runway, 177' left of centerline, up to 12' AGL/471' MSL. Multiple trees and bushes beginning 50' from departure end of runway, 273' left of centerline, up to 50' AGL/551' MSL. Obstruction light 1366' from departure end of runway, 79' right of centerline, 30' AGL/528' MSL. Multiple poles beginning 3065' from departure end of runway, 644' left of centerline, up to 45' AGL/623' MSL. Multiple trees beginning 4155' from departure end of runway, 184' right of centerline, up to 50' AGL/714' MSL.

Rwy 23, tree 2.44 NM from departure end of runway, 747' right of centerline, 100' AGL/1264' MSL. Tree 2.82 NM from departure end of runway, 1753' right of centerline, 60' AGL/819' MSL. Tree 2.73 NM from departure end of runway, 2001' left of centerline, 60' AGL/919' MSL. Tree 2.03 NM from departure end of runway, 2006' left of centerline, 100' AGL/919' MSL. Pole 8021' from departure end of runway, 867' left of centerline, 42' AGL/642' MSL. **Rwy 35**, tree 2990' from departure end of runway, 1030' right of centerline, 50' AGL/648' MSL. Tree 3033' from departure end of runway, 740' right of centerline, 50' AGL/637' MSL. Tree 2497' from departure end of runway, 1106' right of centerline, 50' AGL/615' MSL. Tree 3835' from departure end of runway, 76' right of centerline, 50' AGL/620' MSL. Tree 3041' from departure end of runway, 728' right of centerline, 50' AGL/600' MSL. Tree 3569' from departure end of runway, 116' right of centerline, 50' AGL/596' MSL. Bush 28' from departure end of runway, 289' left of centerline, 15' AGL/461' MSL. Multiple bushes and trees 48' from departure end of runway, 48' right of centerline, up to 200' AGL/648' MSL. Multiple bushes and trees 28' from departure end of runway, 34' left of centerline up to 41' AGL/489' MSL. Multiple bushes beginning 107' from departure end of runway, 133' right of centerline, up to 15' AGL/492' MSL. Multiple bushes beginning 133' from departure end of runway, 43' left of centerline, up to 15' AGL/517' MSL. Road/vehicle 200' from departure end of runway, 62' right of centerline, 15' AGL/487' MSL. Pole 1.32 NM from departure end of runway, 867' left of centerline, 42' AGL/642' MSL.

KOSRAE, FM

KOSRAE (TTK)

ORIG-A 09071 (FAA)

CAUTION: Ships with masts to 200' traverse harbor entrance located on west side of runway.

DEPARTURE PROCEDURE: **Rwy 5**, left turn. **Rwy 23**, right turn, climb to 2000 or above before turning east.

LANAI CITY, HI

LANAI (LNY)

AMDT 5 09239 (FAA)

TAKE-OFF MINIMUMS: **Rwy 3**, 400-1 or std. w/ min. climb of 370' per NM to 2700 or 2500-3 for climb in visual conditions.

DEPARTURE PROCEDURE: **Rwy 3**, climb heading 033° to 1720 before turning left. Climb heading 300° or 180° to intercept route or airway, then continue as cleared. Maintain maximum 210 kts until turn is completed or for climb in visual conditions cross LNY VORTAC eastbound at or above 3700. **Rwy 21**, climb heading 213° to assigned altitude. Eastbound - climb westbound to cross LNY VORTAC eastbound at or above 2700 and climb as cleared. Westbound - climb direct LNY VORTAC then via assigned route.

NOTE: **Rwy 3**, multiple poles, trees, and terrain beginning 2108' from DER, 1011' left of centerline, up to 200' AGL/2202' MSL. **Rwy 21**, lighted windsock 8' from DER, 191' right of centerline, 30' AGL/1323' MSL.

LIHUE, HI

LIHUE (LIH)

AMDT 8 00279 (FAA)

TAKE-OFF MINIMUMS: **Rwy 21**, 2400-3. Use DIANE DEPARTURE PROCEDURE.

DEPARTURE PROCEDURE: **Rwys 3, 35**, to V15, climb runway heading to 500 then climbing right turn, heading 125°, then as assigned. **Rwy 17**, to V15, climb runway heading to 500 then climbing left turn, heading 045°, then as assigned. To LIH-150 climb runway heading to 500 then climbing left turn, heading 120°, then as assigned. **Rwy 21**, to V15, climb runway heading to 550 then climbing left turn, heading 090°, to intercept LIH R-110, maintain 5000, direct BOOKE INT or as assigned. To LIH-148, climb runway heading to 550, then climbing left turn, heading 120°, to intercept LIH R-148, maintain 3000, direct NAPUA INT or as assigned.

POHNPEI ISLAND, FM

POHNPEI INTL (PNI)

AMDT 2 80079 (FAA)

TAKE-OFF MINIMUMS: **Rwys 9, 27**, 400-1½.

DEPARTURE PROCEDURE: **Rwy 9**, climb runway heading to 500 then left turn for north or west departure. **Rwy 27**, climb runway heading to 500 then right turn for north or east departure. Climb runway heading to 1500 before turning for south departure.

CAUTION: Ships with superstructure to 150', traverse Ponape channel, 400' off approach end of Rwy 9, closing airport at times.

**SAIPAN, CQ**

FRANCISCO C. ADA/SAIPAN INTL (GSN)

ORIG-A 09071 (FAA)

DEPARTURE PROCEDURE: **Rwys 7, 25**, climb on runway heading to 1600 before climbing on course.**ROTA INTL (GRO)**

AMDT 1A 09071 (FAA)

DEPARTURE PROCEDURE: **Rwy 9**, climb runway heading to 1000 before turning. **Rwy 27**, climb runway heading to 2000 or above before turning south.**TINIAN ISLAND, CQ**

TINIAN INTL (TNI)

AMDT 1 09239 (FAA)

NOTE: **Rwy 8**, trees beginning 694' from DER, 507' left of centerline, up to 100' AGL/363' MSL. Multiple trees beginning 569' from DER, 471' right of centerline, up to 100' AGL/389' MSL. **Rwy 26**, multiple trees beginning 743' from DER, 508' right of centerline, up to 100' AGL/363' MSL.**TUTUILA, AQ**

PAGO PAGO INTL (PPG)

ORIG-A 09071 (FAA)

TAKE-OFF MINIMUMS: **Rwy 23**, std. w/ min. climb of 320' per NM to 800, or 2700-3 for climb in visual conditions. **Rwy 26**, NA-obstacles.DEPARTURE PROCEDURE: **Rwys 5, 8**, climbing right turn southbound between TUT R-090 clockwise to R-180 to 2800, then proceed on course. **Rwy 23**, climbing left turn heading 150° southbound between TUT R-090 clockwise to R-180 to 2800, then proceed on course. For climb in visual conditions: cross Pago Pago Intl Airport at or above 2600 before proceeding on course.NOTE: **Rwy 5**, bush 1' from departure end of runway, 237' right of centerline, 3' AGL/12' MSL. Bush 379' from departure end of runway, 362' left of centerline, 14' AGL/23' MSL. Ship 998' from departure end of runway, 57' right of centerline, 150' AGL/150' MSL. **Rwy 8**, bush 689' from departure end of runway, 360' left of centerline, 15' AGL/23' MSL. Ship 1435' from departure end of runway, 304' left of centerline, 150' AGL/150' MSL. **Rwy 23**, multiple trees beginning 352' from departure end of runway, 173' left of centerline, up to 20' AGL/132' MSL. Multiple trees beginning 881' from departure end of runway, 296' right of centerline, up to 20' AGL/172' MSL. Multiple trees and poles beginning 1.6 NM from departure end of runway, 38' right of centerline, up to 367' AGL/554' MSL. Tree 2.3 NM from departure end of runway, 2126' left of centerline, 20' AGL/387' MSL.**WENO ISLAND, FM**

CHUUK INTL (TKK)

AMDT 2 10042(FAA)

DEPARTURE PROCEDURE: **Rwy 4**, climb heading 041° to 1100 before proceeding on course. **Rwy 22**, climb heading 221° to 1500 before proceeding on course.NOTE: **Rwy 4**, bush 205' from DER, 203' right of centerline, 7' AGL/17' MSL. **Rwy 22**, bush 5' from DER, 241' right of centerline, 14' AGL/24' MSL. Bush 221' from DER, 85' right of centerline, 7' AGL/17' MSL. **CAUTION:** Ships with superstructure to 150' traverse channels west of runway 4/22.**YAP ISLAND, FM**


YAP INTL (T11)

AMDT 2 94342 (FAA)

DEPARTURE PROCEDURE: **Rwys 7**, climbing right turn to 1500 via 090° bearing from YP NDB/DME, then climb on course. **Rwy 25**, climb to 500, then climb on course.

LINDBERG ONE DEPARTURE (OBSTACLE) (RNAV)

HCF APPROACH
126.0 278.3
CLNC DEL 122.3
CTAF 122.9



NOTE: RNAV 1.

NOTE: GPS required.

NOTE: Do not exceed 200 KIAS until LNBRG.

TAKE-OFF MINIMUMS

Rwy 26: NA.

Rwy 8: Standard.

TAKE-OFF OBSTACLE NOTE

Rwy 8: Multiple trees and bushes beginning 122' from DER,
75' right of centerline, up to 50' AGL/139' MSL.

NOTE: Chart not to scale

DEPARTURE ROUTE DESCRIPTION

TAKE-OFF RUNWAY 8: Climb via 079° course to SIPAE, then right turn direct LNBRG, thence. . . .

. . . .climb in holding (if required) to cross LNBRG at or above 5400 before proceeding via assigned route.

RNAV (GPS) RWY 26


HANA(HNM)(PHN)

APP CRS	Rwy Idg	3606
259°	TDZE	70
	Apt Elev	78



▼ Circling NA S of Rwy 8-26.
DME/DME RNP-0.3 NA.
Procedure NA at night.

MISSED APPROACH: Climbing right turn to 2500 direct GPYLE and hold.

AWOS-3 118.325	HCF APPROACH 126.0 278.3	CLNC DEL 122.3	CTAF 122.9 ①
--------------------------	------------------------------------	--------------------------	-------------------------------



ELEV 78



CATEGORY	A	B	C	D
RNAV MDA	660-1	590 (600-1)	NA	NA
CIRCLING	660-1 582 (600-1)	760-1 682 (700-1)	NA	NA

MIRL Rwy 8-26 **①**

AIRPORT DIAGRAM


AL-756 (FAA)

HILO INTL (ITO)(PHTO)
HILO, HAWAII

ATIS
126.4
HILO TOWER★
118.1 263.1
GND CON
121.9



JANUARY 2005
ANNUAL RATE OF CHANGE
0.0° W



RWY 3-21
S75, D80, DT140, SBTT230, DDT410
RWY 8-26
S75, D250, DT350, SBTT450, DDT850

CAUTION: BE ALERT TO RUNWAY CROSSING CLEARANCES.
READBACK OF ALL RUNWAY HOLDING INSTRUCTIONS IS REQUIRED.

155°03'W

155°02'W

283

PAC: 08 APR 2010 to 03 JUN 2010

ILS or LOC RWY 26

HILO INTL (ITO) (PHTO)


LOC/DME I-ITO 110.7 Chan 44	APP CRS 259°	Rwy Idg TDZE Apt Elev	9800 38 38
---	------------------------	-----------------------------	---------------------------------------

⚠ Circling not authorized south of Rwy 8-26. For inoperative MALS/R increase S-LOC 26 vis to 1 mile all Cats. Inoperative table does not apply to S-ILS 26. ADF or DME required.


MALSRS

MISSED APPROACH: Climb to 450 then climbing right turn to 3000 via ITO R-002 then direct ITO VORTAC and hold.

ATIS 126.4	HILO APP CON 119.7 269.2	HILO TOWER★ 118.1(CTAF) 263.1	GND CON 121.9
----------------------	------------------------------------	---	-------------------------



ELEV **38**




REIL Rwy 3
MIRL Rwy 3-21
HIRL Rwy 8-26

FAF to MAP 6 NM


Knots	60	90	120	150	180
Min:Sec	6:00	4:00	3:00	2:24	2:00


ADF or DME REQUIRED




CATEGORY	A	B	C	D
S-ILS 26		288-1	250 (300-1)	
S-LOC 26		420-¾	382 (400-¾)	
CIRCLING	500-1	462 (500-1)	500-1½ 462 (500-1½)	700-2 662 (700-2)


ATIS 126.4
GND CON
121.9
HILO TOWER *
118.1 (CTAF) 263.1
HILO DEP CON
119.7 269.2

UPOLU POINT
112.3 UPP 
Chan 70



SAPDE
N20° 09.29'
W154° 57.76'



HILO
116.9 ITO 
Chan 116
N19°43.28'-W155°00.66'

PAHOA
332 POA 

TAKE OFF MINIMUMS:

- Rwy 3, 8: STANDARD
- Rwy 21: Standard with minimum climb of 310' per NM to 1100 or 1300-2½ for climb in visual conditions.
- Rwy 26: Standard with minimum climb of 385' per NM to 2900 or 1300-2½ for climb in visual conditions.

NOTE: Chart not to scale.

(NARRATIVE ON FOLLOWING PAGE)

PAC: 08 APR 2010 to 03 JUN 2010

▼

DEPARTURE ROUTE DESCRIPTION

TAKE-OFF RUNWAY 3: Climb heading 030° and ITO R-355 to SAPDE INT, thence....

TAKE-OFF RUNWAY 8: Climb heading 079° to ITO VORTAC and ITO R-355 to SAPDE INT, thence....

TAKE-OFF RUNWAY 21: Climbing left turn direct ITO VORTAC and ITO R-355 to SAPDE INT, or climb in visual conditions to cross ITO VORTAC northbound at or above 1200 MSL, then via R-355 to SAPDE INT, thence....

TAKE-OFF RUNWAY 26: Climbing right turn via heading 045° and ITO R-355 to SAPDE INT, or climb in visual conditions to cross ITO VORTAC northbound at or above 1200 MSL, then via R-355 to SAPDE INT, thence....

...proceed via UPP R-082 to PARIS INT.

TAKE OFF OBSTACLE NOTES

Rwy 3: Numerous trees and WSK beginning 395' from DER, 68' left of centerline, up to 86' AGL/115' MSL.

Numerous trees beginning 325' from DER, 137' right of centerline, up to 66' AGL/95' MSL.

Rwy 8: Tree 1198' from DER, 480' left of centerline, 37' AGL/70' MSL.

Numerous trees beginning 414' from DER, 328' right of centerline, up to 46' AGL/79' MSL.

Rwy 21: Numerous trees and poles beginning 1077' from DER, 272' left of centerline, up to 70' AGL/490' MSL.

Numerous trees and poles beginning 236' from DER, 43' right of centerline, up to 83' AGL/362' MSL.

Vehicles on road beginning 234' from DER, 260' left of centerline, 15' AGL/58' MSL.

Rwy 26: Numerous vehicles beginning 6' from DER, 452' right of centerline, up to 15' AGL/39' MSL.

Numerous trees and light poles beginning 542' from DER, 471' left of centerline, up to 86' AGL/92' MSL.

Numerous trees beginning 1645' from DER, 266' right of centerline, up to 93' AGL/119' MSL.

Windsock 3' from DER, 269' right of centerline, 19' AGL/46' MSL.

Radar reflector 373' from DER, 346' right of centerline, 10' AGL/37' MSL.



RNAV (GPS) RWY 21

HILO INTL (ITO) (PHTO)

APP CRS	Rwy Idg	5600
210°	TDZE	31
	Apt Elev	38

⚠ **⚠** NA Circling not authorized south of Rwy 8-26. MISSED APPROACH: Climbing left turn to 5000 direct POA NDB and hold.

ATIS 126.4	HILO APP CON 119.7 269.2	HILO TOWER ★ 118.1 (CTAF) 263.1	GND CON 121.9
----------------------	------------------------------------	---	-------------------------



CATEGORY	A		B		C		D	
	LN	AV	LN	AV	LN	AV	LN	AV
LN	440-1	409 (500-1)	440-1	409 (500-1)	440-1 1/4	409 (500-1 1/4)	700-2	662 (700-2)
AV	500-1	462 (500-1)	500-1 1/2	462 (500-1 1/2)	500-1 1/2	462 (500-1 1/2)	700-2	662 (700-2)

RNAV (GPS) RWY 26

HILO INTL (ITO) (PHTO)

APP CRS **259°**
 Rwy Idg **9800**
 TDZE **38**
 Apt Elev **38**

▽ Circling not authorized south of Rwy 8-26.
 For inoperative MALSRL increase LNAV Cat A, B & D ¼ mile.
△NA Baro-VNAV NA below -5°C (23°F).
 GPS or RNP-0.3 Required. DME/DME RNP-0.3 NA.
 WAAS VNAV NA.

MALSRL




MISSED APPROACH: Climb to 5000
 direct EKAGE WP then right turn
 direct ARBOR WP and hold.

ATIS
126.4



HILO APP CON
119.7 269.2

HILO TOWER★
118.1(CTAF) 263.1

GND CON
121.9



ELEV **38**



CATEGORY	A	B	C	D
GLS PA DA	NA			
LNAV/ VNAV DA	440-1 402 (500-1)			
LNAV MDA	440-3/4	402 (500-3/4)	440-1 402 (500-1)	
CIRCLING	500-1 1/2	462 (500-1 1/2)	700-2 662 (700-2)	





REIL Rwy 3
 MIRL Rwy 3-21
 HIRL Rwy 8-26

VORTAC ITO 116.9 Chan 116	APP CRS 259°	Rwy Idg TDZE Apt Elev	N/A N/A 38
---	------------------------	-----------------------------	---------------------------------------

▽ Circling not authorized south of Rwy 8-26.

MISSED APPROACH: Climbing right turn to 3000 via ITO R-002 then direct to ITO VORTAC and hold.

ATIS 126.4	HILO APP CON 119.7 269.2	HILO TOWER ★ 118.1 (CTAF) 263.1	GND CON 121.9
----------------------	------------------------------------	---	-------------------------



FAF to MAP 1 NM						CATEGORY		A		B		C		D	
Knots	60	90	120	150	180	CIRCLING		500-1		462 (500-1)		500-1½		700-2	
Min:Sec	1:00	0:40	0:30	0:24	0:20							462 (500-1½)		662 (700-2)	

VOR/DME or TACAN-A





HILO INTL (ITO) (PHTO)

VORTAC ITO	APP CRS	Rwy Idg	N/A
116.9	145°	TDZE	N/A
Chan 116		Apt Elev	38

▼ Circling not authorized south of Rwy 8-26.

MISSED APPROACH: Climbing left turn to 3000 via ITO R-079 to VEWES/5 DME and hold.

ATIS 126.4	HILO APP CON 119.7 269.2	HILO TOWER ★ 118.1 (CTAF) 263.1	GND CON 121.9
----------------------	------------------------------------	---	-------------------------



CATEGORY	A	B	C	D	REIL Rwy 3
CIRCLING	500-1½		462 (500-1½)	700-2	MIRL Rwy 3-21
				662 (700-2)	HIRL Rwy 8-26

VOR/DME or TACAN RWY 26




HILO INTL (ITO) (PHTO)

VORTAC ITO 116.9 Chan 116	APP CRS 259°	Rwy Idg TDZE Apt Elev 9800 38 38
---	------------------------	--

⚠ Circling not authorized south of Rwy 8-26. Visibility reduction for helicopters NA. For inoperative MALSRR increase S-26 Cat. A/B and D visibility ¼ mile.

MALSRR **AS**
MISSED APPROACH: Climbing right turn to 3000 via ITO R-079 to VEWES/5 DME and hold.

ATIS 126.4	HILO APP CON 119.7 269.2	HILO TOWER ★ 118.1 (CTAF) 263.1	GND CON 121.9
----------------------	------------------------------------	--	-------------------------




CATEGORY	A	B	C	D
S-26	460-¾ 422 (500-¾)			460-1 422 (500-1)
CIRCLING	500-1½ 462 (500-1½)			700-2 662 (700-2)

REIL Rwy 3
MIRL Rwy 3-21
HIRL Rwy 8-26

AIRPORT DIAGRAM

AL-754 (FAA)

HONOLULU INTL (HNL) (PHNL)
HONOLULU, HAWAII



ATIS 127.9 251.15
HONOLULU TOWER 118.1 257.8
GND CON 121.9 348.6
GND CON (RAMP CON) 121.8
CINC DEL 121.4

HICKAM AFB
BASE OPS


CAUTION: BE ALERT TO RUNWAY CROSSING CLEARANCES.
REARBACK OF ALL RUNWAY HOLDING INSTRUCTIONS IS REQUIRED.

ASDE-X Surveillance System in use.
Pilots should operate transponders with Mode C on all twys and twys.

HICKAM RAMP ADVISORY

RWY 4L-22R S100, D200, ST175, DT400, DD1850
RWY 4R-22L S100, D200, ST175, DT400, DD1850
RWY 8L-26R S100, D200, ST175, TT345, DT400, SBT1593, TR1566, DD1780, TD1840
RWY 8R-26L S80, D170, ST175, DT400, TT488, DD1780

HCF APPROACH
 118.3 269.0
 ATIS
 127.9 251.15



NOTE: RNAV equipped aircraft only DANNO and THOMA transitions.
 NOTE: DME REQUIRED
 NOTE: Chart not to scale

ARRIVAL DESCRIPTION

CANON TRANSITION (CANON.BOOKE8): From over CANON INT via SOK R-277 to SOK VORTAC. Then via SOK R-102 to BOOKE DME. Thence....

DANNO TRANSITION (DANNO.BOOKE8): From over DANNO WP via RNAV 116° course to LIH VORTAC. Then via LIH R-110 to BOOKE DME. Thence....


SYVAD TRANSITION (SYVAD.BOOKE8): From over SYVAD INT via SOK R-260 to SOK VORTAC. Then via SOK R-102 to BOOKE DME. Thence....

THOMA TRANSITION (THOMA.BOOKE8): From over THOMA WP via RNAV 135° course to LIH 123 DME, then LIH R-315 to LIH VORTAC. Then via LIH R-110 to BOOKE DME. Thence....

....From over BOOKE DME via LIH R-110 and HNL R-258 to HNL VORTAC. Expect radar vectors.

PAC. 08 APR 2010 to 03 JUN 2010

HONOLULU ONE DEPARTURE (OBSTACLE)



ATIS
127.9 251.15
CLNC DEL
121.4 281.4
GND CON
121.9 348.6
HONOLULU TOWER
118.1 257.8

TAKE-OFF MINIMUMS:

- RWYS 22L/R, 26R: Standard.
- RWYS 4L/R: Standard with minimum climb of 425 feet per NM to 1900, do not exceed 180 KIAS until southeast bound on 155° heading, or 1700-2½ for climb in visual conditions.
- RWY 8L: Standard with minimum climb of 310 feet per NM to 1000, or 1700-2½ for climb in visual conditions.
- RWY 8R: Standard with minimum climb of 270 feet per NM to 1000, or 1700-2½ for climb in visual conditions.
- RWY 26L: Standard with minimum climb of 237 feet per NM to 300, or 1700-2½ for climb in visual conditions.

(NARRATIVE ON FOLLOWING PAGE)

NOTE: Chart not to scale.



DEPARTURE ROUTE DESCRIPTION

TAKE-OFF RUNWAYS 4L/R, 8L/R: Climbing right turn to 3000 via heading 155° to intercept HNL R-125 to HAUNA INT before proceeding on course, or....

TAKE-OFF RUNWAYS 22L/R, 26L/R: Climbing left turn to 3000 via heading 140° to intercept HNL R-171 to ALANA INT before proceeding on course, or....

....For climb in visual conditions to cross HNL VORTAC southbound at 1600, continue climb to 3000 via HNL R-171 to ALANA INT before proceeding on course.

PAC. 08 APR 2010 to 03 JUN 2010

TAKE-OFF OBSTACLE NOTES:

RWY 4L: Multiple lights beginning 630 feet from DER, 236 feet left of centerline, 102 feet right of centerline, up to 84 feet AGL/92 feet MSL. Light on bldg 669 feet from DER, 394 feet left of centerline, 29 feet AGL/37 feet MSL. Stack on bldg 2,488 feet from DER, 219 feet right of centerline, 72 feet AGL/80 feet MSL. Multiple trees beginning 1,253 feet from DER, 209 feet left of centerline, 935 feet right of centerline, up to 64 feet AGL/72 feet MSL. Bush 450 feet from DER, 234 feet left of centerline, 14 feet AGL/22 feet MSL.

RWY 4R: Stack on bldg, 2,442 feet from DER, 283 feet left of centerline, 72 feet AGL/80 feet MSL. Multiple trees beginning 1,206 feet from DER, 711 feet left of centerline, 433 feet right of centerline, up to 64 feet AGL/72 feet MSL. Multiple lights beginning 1,072 feet from DER, 399 feet left of centerline, 504 feet right of centerline, up to 36 feet AGL/44 feet MSL. Pole 2,110 feet from DER, 951 feet left of centerline, 59 feet AGL/67 feet MSL.

RWY 22L: Multiple bushes beginning 265 feet from DER, 396 feet right of centerline, 17 feet AGL/31 feet MSL. Tree 1,065 feet from DER, 499 feet right of centerline, 30 feet AGL/38 feet MSL.

RWY 22R: Rod on OL ASR 1,451 feet from DER, 827 feet right of centerline, 76 feet AGL/84 feet MSL. Tree 853 feet from DER, 308 feet right of centerline, 43 feet AGL/51 feet MSL.

RWY 26L: Ship 6,683 feet from DER, on centerline, 208 feet AGL/208 feet MSL.

ILS RWY 4R

HONOLULU INTL (HNL) (PHNL)




LOC/DME HUM 110.5 Chan 42	APP CRS 042°	Rwy Idg TDZE Apt Elev	9000 9 13
---	------------------------	-----------------------------	--------------------------------------

⚠ Cat. A, B, C circling not authorized northwest of airport between Rwys 8L-26R and 4L- 22R. Cat. D, E circling not authorized north of Rwy 8L-26R. For inoperative MALSRL, increase S-ILS-4R Cat. E visibility to 1/4 and S-LOC-4R visibility to 1/2.


MALSRL
(AS)

MISSED APPROACH: Climb to 500 then climbing right turn to 3000 via HNL R-171 to ALANA Int/HNL 13.9 DME and hold.

ATIS 127.9 251.15	HCF APPROACH 118.3 269.0	HONOLULU TOWER 118.1 257.8	GND CON 121.9 348.6	CLNC DEL 121.4 281.4	RAMP CONTROL 121.8
-----------------------------	------------------------------------	---	-------------------------------	--------------------------------	------------------------------



ELEV 13	SEALANES: 8W-26W 5000 X 300 4W-22W 3000 X 150
----------------	--



CATEGORY	A	B	C	D	E
S-ILS 4R	209-1/2		200 (200-1/2)		359-1 350 (400-1)
S-LOC 4R	460-1/2	451 (500-1/2)	460-3/4 451 (500-3/4)	460-1 451 (500-1)	
CIRCLING	620-1 607 (700-1)		620-1 3/4 607 (700-1 3/4)	760-2 1/2 747 (800-2 1/2)	1500-3 1487 (1500-3)

MIRL Rwy 4L-22R REIL Rwys 4L, 8R, 22L, 22R and 26R HIRL Rwys 4R-22L, 8L-26R and 8R-26L	FAF to MAP 4 NM					
	Knots	60	90	120	150	180
	Min:Sec	4:00	2:40	2:00	1:36	1:20

ILS RWY 8L


HONOLULU INTL (HNL)(PHNL)

LOC I-HNL 111.7	APP CRS 079°	Rwy Idg 12300 TDZE 13 Apt Elev 13
---------------------------	------------------------	--


▼ Cat. A, B, C circling not authorized northwest of airport between Rwy 8L-26R and 4L-22R; Cat. D circling not authorized north of Rwy 8L-26R.

MALS R (AS) MISSED APPROACH: Climb to 500 then climbing right turn to 3000 via HNL R-171 to ALANA Int/HNL 13.9 DME and hold.

ATIS 127.9 251.15	HCF APPROACH 118.3 269.0	HONOLULU TOWER 118.1 257.8	GND CON 121.9 348.6	CLNC DEL 121.4 281.4	RAMP CONTROL 121.8
-----------------------------	------------------------------------	--------------------------------------	-------------------------------	--------------------------------	------------------------------




ELEV 13	SEALANES: 8W-26W 5000 X 300 4W-22W 3000 X 150
----------------	---



MIRL Rwy 4L-22R
REIL Rwy 4L, 8R, 22L, 22R and 26R
HIRL Rwy 4R-22L, 8L-26R and 8R-26L


FAF to MAP 5.9 NM					
Knots	60	90	120	150	180
Min:Sec	5:54	3:56	2:57	2:22	1:58



CATEGORY	A	B	C	D
S-ILS 8L	213-1/2 200 (200-1/2)			
S-LOC 8L	460-1/2	447 (500-1/2)	460-3/4 447 (500-3/4)	460-1 447 (500-1)
CIRCLING	620-1	607 (700-1)	620-1 3/4 607 (700-1 3/4)	760-2 1/2 747 (800-2 1/2)

JULLE FOUR ARRIVAL (JULLE.JULLE4)

HC F APPROACH
118.3 269.0
ATIS
127.9 251.15



NOTE: Chart not to scale.

CHAIN TRANSITION (CHAIN.JULLE4): From over CHAIN INT via LNY 13 DME Arc to intercept LNY R-278 to JULLE INT. Thence....

DOVRR TRANSITION (DOVRR.JULLE4): From over DOVRR INT via MKK R-180 to JORDA INT, thence via HNL R-125 to JULLE INT. Thence....

FIRES TRANSITION (FIRES.JULLE4): From over FIRES INT via HNL R-125 to JULLE INT. Thence....

LANAI TRANSITION (LNY.JULLE4): From over LNY VORTAC via LNY R-278 to JULLE INT. Thence....


UPOLU TRANSITION (UPP.JULLE4): From over UPP VORTAC via UPP R-272 and HNL R-125 to JULLE INT. Thence....

....From over JULLE INT via LNY R-278 to ALANA INT. Expect vectors to final approach course.

LOST COMMUNICATIONS: After ALANA INT via HNL R-171 to HNL VORTAC maintain 4000 feet.

PAC. 08 APR 2010 to 03 JUN 2010

KEAHI THREE DEPARTURE (KEAHI3.KEAHI)



PAC. 08 APR 2010 to 03 JUN 2010

DEPARTURE ROUTE DESCRIPTION

- TAKE-OFF RUNWAYS 22/26 ONLY:** Turn left to heading assigned by tower, expect radar vectors to intercept HNL R-138; then via HNL R-138 to KEAHI INT, maintain 5000'; then via (transition). Expect clearance to enroute altitude/flight level at JORDA INT or LNY VORTAC.
- JORDA TRANSITION (KEAHI3.JORDA):** From over KEAHI INT via LNY R-262 and HNL R-125 to JORDA INT.
- LANAI TRANSITION (KEAHI3.LNY):** From over KEAHI INT via LNY R-262 to LNY VORTAC.
- UPOLU TRANSITION (KEAHI3.UPP):** From over KEAHI INT via LNY R-262 and HNL R-125 to JORDA INT, thence via UPP R-278 to UPP VORTAC.

KEOLA TWO DEPARTURE (KEOLA2.KEOLA)

DEPARTURE ROUTE DESCRIPTION

Turn right/left to heading assigned by the Tower, expect vectors to KEOLA INT, maintain 5000'; then via transitions. Expect clearance to enroute altitude/flight level at KEOLA INT.

KATHS TRANSITION (KEOLA2.KATHS): Via HNL R-258 and SOK R-234 to KATHS INT.


LIHUE TRANSITION (KEOLA2.LIH): Via SOK R-111 and LIH R-148 to LIH VORTAC.

LILIA TRANSITION (KEOLA2.LILIA): Via RNAV course 282° to LILIA WP.

NONNI TRANSITION (KEOLA2.NONNI): Via HNL R-258 to NONNI INT.

PUPPI TRANSITION (KEOLA2.PUPPI): Via RNAV course 271° to PUPPI WP.

SOUTH KAUI TRANSITION (KEOLA2.SOK): Via SOK R-111 to SOK VORTAC.




LDA/DME RWY 26L


HONOLULU INTL (HNL) (PHNL)

LOC/DME I-EPC 109.1 Chan 28	APP CRS 304°	Rwy Idg 12000 TDZE 10 Apt Elev 13
--	------------------------	--


⚠ Cat. A, B, C circling not authorized northwest of airport between Rws 8L/26R and 4L/22R. Cat. D, E circling not authorized north of Rwy 8L/26R.
⚠ Inoperative table does not apply to MALSF. Follow flasher lights to Rwy 26L.
 Procedure not authorized at night when MALSF inoperative.

MALSF

MISSED APPROACH: Climbing left turn to 3000 via HNL R-171 to ALANA Int/HNL 13.9 DME and hold.

ATIS 127.9 251.15	HCF APPROACH 118.3 269.0	HONOLULU TOWER 118.1 257.8	GND CON 121.9 348.6	CLNC DEL 121.4 281.4	RAMP CONTROL 121.8
-----------------------------	------------------------------------	---	-------------------------------	--------------------------------	------------------------------




ELEV 13	SEALANES: 8W-26W 5000 X 300 4W-22W 3000 X 150
----------------	---



CATEGORY	A	B	C	D	E
S-26L	560-2 550 (600-2)				
CIRCLING	620-2 607 (700-2)		760-2½ 747 (800-2½)		1500-3 1487 (1500-3)

MIRL Rwy 4L-22R
 REIL Rws 4L, 8R, 22L, 22R and 26R
 HIRL Rws 4R-22L, 8L-26R and 8R-26L

MAGGI THREE ARRIVAL (MAGGI.MAGGI3)



ARRIVAL DESCRIPTION

APACK TRANSITION (APACK.MAGGI3): From over APACK DME via MKK R-004 to MAGGI INT. Thence....

BITTA TRANSITION (BITTA.MAGGI3): From over BITTA DME via MKK R-022 to intercept CKH R-039 to MAGGI INT. Thence....


CLUTS TRANSITION (CLUTS.MAGGI3): From over CLUTS DME via heading 240° to intercept CKH R-039 to MAGGI INT. Thence....

DENNS TRANSITION (DENNS.MAGGI3): From over DENNS INT via heading 260° to intercept CKH R-039 to MAGGI INT. Thence....

ZIGIE TRANSITION (ZIGIE.MAGGI3): From over ZIGIE DME via heading 156° to intercept MKK R-004 to MAGGI INT. Thence....

....From over MAGGI INT via CKH R-039 to CKH VORTAC then radar vectors for approach to airport.

MOLOKAI FOUR DEPARTURE (MKK4.MKK)



NOTE: Chart not to scale.

(NARRATIVE ON FOLLOWING PAGE)

PAC. 08 APR 2010 to 03 JUN 2010

NOTE: Departures from Rwy's 26L/R must complete left turn to assigned heading within 2 NM of runway departure end (HNL 3 DME). Cross egress fixes at assigned cruising altitude.

NOTE: Departures from Rwy's 4L/R and 8L/R must complete right turn to assigned heading within 2 NM of runway departure end (HNL 3.6 DME). Cross CKH R-240 at or above 2500'.

ZIGIE
N24°18.82'-W157°17.12'
116.1 MKK 347.0°-190.0
1421

HONOLULU HNL
114.8 HNL
Chan 95

KOKO HEAD
113.9 CKH
Chan 86

MOLOKAI
116.1 MKK
Chan 108
N21°08.29'-W157°10.05'
W156°51.35'

UPOLU POINT
112.3 UPP
Chan 70

HILO ITO
116.9 ITO
Chan 116

ZIGIE TRANSITION IS RNAV ONLY

MOLOKAI FOUR DEPARTURE (MKK4.MKK)**DEPARTURE ROUTE DESCRIPTION**

Turn right/left to heading as assigned by Tower, expect vectors to MKK VORTAC, maintain 5000'; then via (transition). Expect clearance to enroute altitude/flight level at MKK VORTAC. Cross egress fixes ZIGIE, APACK, CLUTS, EBBER, and FITES at assigned cruising altitude, unless otherwise advised by ATC.

APACK TRANSITION (MKK4.APACK): From over MKK VORTAC via MKK R-004 to APACK INT.


CLUTS TRANSITION (MKK4.CLUTS): From over MKK VORTAC via MKK R-040 to CLUTS INT.

EBBER TRANSITION (MKK4.EBBER): From over MKK VORTAC via MKK R-056 to BLUSH INT then via 080° heading and R577 to EBBER INT.

FITES TRANSITION (MKK4.FITES): From over MKK VORTAC via MKK R-056 to BLUSH INT then via 095° heading and R578 to FITES INT.

PULPS TRANSITION (MKK4.PULPS): From over MKK VORTAC via MKK R-108 to PULPS INT.

ZIGIE TRANSITION (MKK4.ZIGIE): From over MKK VORTAC via MKK R-004 to intercept and proceed via OGG R-337 to REXIE DME. Then via RNAV heading 334° to ZIGIE WP.




ARRIVAL DESCRIPTION

CARRP TRANSITION (CARRP.OPACA4): From over CARRP WP, RNAV direct to OPACA DME. Thence....

CHOKO TRANSITION (CHOKO.OPACA4): From over CHOKO WP, RNAV direct to BINJO DME, then direct to OPACA DME. Thence....

KATHS TRANSITION (KATHS.OPACA4): From over KATHS WP, RNAV direct to OPACA DME. Thence....

....From over OPACA DME via HNL R-207 to HNL VORTAC, expect radar vectors to final approach course.



NOTE: Honolulu departures from Rwys 4L/R and 8L/R must complete right turn to assigned heading within 2 NM of departure end of runway (HNL 3.6 DME). Cross CKH R-240 at or above 2500'.

NOTE: Honolulu departures Rwys 26L/R left turn to assigned heading must be completed within 2 NM of departure end of runway (HNL 3 DME).

(NARRATIVE ON FOLLOWING PAGE)

NOTE: Chart not to scale.


OPIHI TWO DEPARTURE (OPIHI2.OPIHI)**DEPARTURE ROUTE DESCRIPTION**

Turn right/left to heading assigned by tower, expect vectors to OPIHI INT, maintain 5000'; then via (transition). Expect clearance to enroute altitude/flight level at OPIHI INT.

CARRP TRANSITION (OPIHI2.CARRP): From over OPIHI INT via right turn to intercept MKK R-254 to HNL R-204, then via HNL R-204 to HNL 100 DME, then via course 204° to CARRP WP.

CHOKO TRANSITION (OPIHI2.CHOKO): From over OPIHI INT via right turn to intercept MKK R-254 to HNL R-241 to BINJO DME, then via course 241° to CHOKO WP.

DOVRR TRANSITION (OPIHI2.DOVRR): From over OPIHI INT via HNL R-187 to HNL 50 DME, then via left turn heading 153° RNAV course to DOVRR WP.



ATIS
 127.9 251.15
 CLNC DEL
 121.4 281.4
 GND CON
 121.9 348.6
 HONOLULU TOWER
 118.1 257.8
 HCF APPROACH
 NORTH 119.1 239.05
 EAST 124.8 317.6
 WEST 118.3 269.0

NOTE: Departures from Runways 4L/R and 8L/R must complete right turn to assigned heading within 2 NM of runway departure end (HNL 3.6 DME). Cross CKH R-240 at or above 2500'. Departures from Runways 26L/R must complete left turn to assigned heading within 2 NM of runway departure end (HNL 3 DME).

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

Turn right/left to heading as assigned by tower, expect vectors to PALAY INT, maintain 5000'; then via (transition). Expect clearance to enroute altitude/flight level at LNY VORTAC.

LANAI TRANSITION (PALAY2.LNY): From over PALAY INT via HNL R-110 and LNY R-290 to LNY VORTAC.

MOLOKAI TRANSITION (PALAY2.MKK): From over PALAY INT via MKK R-254 to MKK VORTAC.

PAC. 08 APR 2010 to 03 JUN 2010

RNAV (GPS) RWY 4L


HONOLULU INTL (HNL) (PHNL)

APP CRS	Rwy Idg	6398
042°	TDZE	10
	Apt Elev	13



GPS or RNP-0.3 Required. DME/DME RNP-0.3 NA. Cats. A, B, C circling not authorized northwest of airport between Rwy 8L-26R and 4L-22R. Cats. D, E circling not authorized north of Rwy 4L-22R.

MISSED APPROACH: Climb to 500 then climbing right turn to 3000 direct to ALANA WP and hold.

ATIS	HCF APPROACH	HONOLULU TOWER	GND CON	CLNC DEL	RAMP CONTROL
127.9 251.15	118.3 269.0	118.1 257.8	121.9 348.6	121.4 281.4	121.8



ELEV	13
SEALANES:	8W-26W 5000 X 300 4W-22W 3000 X 150



MIRL Rwy 4L-22R					
REIL Rwy 4L, 8R, 22L, 22R and 26R					
HIRL Rwy 4R-22L, 8L-26R and 8R-26L					
CATEGORY	A	B	C	D	E
LNNAV MDA	460-1¼	450 (500-1¼)		460-1½	450 (500-1½)
CIRCLING	620-1¼	607 (700-1¼)	620-1¾ 607 (700-1¾)	820-2½ 807 (900-2½)	1500-3 1487 (1500-3)

RNAV (GPS) RWY 8R


HONOLULU INTL (HNL) (PHNL)

APP CRS	Rwy Idg	12000
079°	TDZE	10
	Apt Elev	13




▼ Cat. A, B, C circling NA northwest of airport between Rwys 8L-26R and 4L-22R. Cat. D, E circling NA north of Rwy 4L-22R.
▲ NA
 GPS or RNP-0.3 Required. DME/DME RNP-0.3 NA.

MISSED APPROACH: Climb to 500 then climbing right turn to 3100 direct ALANA WP and hold.

ATIS	HCF APPROACH	HONOLULU TOWER	GND CON	CLNC DEL	RAMP CONTROL
127.9 251.15	118.3 269.0	118.1 257.8	121.9 348.6	121.4 281.4	121.8



ELEV	13
D	SEALANES: 8W-26W 5000 X 300 4W-22W 3000 X 150



MIRL Rwy 4L-22R
 REIL Rwys 4L, 8R, 22L, 22R and 26R
 HIRL Rwys 4R-22L, 8L-26R and 8R-26L

CATEGORY	A	B	C	D	E
LNNAV MDA	320-1 310 (400-1)				
CIRCLING	620-1	607 (700-1)	620-1 ³ / ₄ 607 (700-1 ³ / ₄)	820-2 ¹ / ₂ 807 (900-2 ¹ / ₂)	1500-3 1487 (1500-3)

RNAV (GPS) Y RWY 4R


HONOLULU INTL (HNL) (PHNL)

APP CRS	Rwy Idg	9000
042°	TDZE	9
	Apt Elev	13



D DME/DME RNP-0.3 NA. For inoperative MALSRL increase Cat E visibility to 1½. Cat A,B,C circling NA NW of airport between Rwy 8L-26R and 4L-22R. Cat D, E circling NA N of Rwy 8L-26R.

MALSRL MISSED APPROACH: Climbing right turn to 5000 direct LUYEV and hold, continue climb-in-hold to 5000.

ATIS	HCF APPROACH	HONOLULU TOWER	GND CON	CLNC DEL	RAMP CONTROL
127.9 251.15	118.3 269.0	118.1 257.8	121.9 348.6	121.4 281.4	121.8



ELEV	13	SEALANES:
		8W-26W 5000 X 300
		4W-22W 3000 X 150



CATEGORY	A	B	C	D	E
LNAV MDA	460-¾	451 (500-¾)		460-1	451 (500-1)
CIRCLING	620-1¼	607 (700-1¼)	620-1¾ 607 (700-1¾)	820-2½ 807 (900-2½)	1500-3 1487 (1500-3)

MIRL Rwy 4L-22R
REIL Rwy 4L, 8R, 22L, 22R and 26R
HIRL Rwy 4R-22L, 8L-26R and 8R-26L

RNAV (GPS) Y RWY 8L

HONOLULU INTL (HNL) (PHNL)


APP CRS	Rwy Idg	12300
079°	TDZE	13
	Apt Elev	13

▼ DME/DME RNP-0.3 NA Cat. A, B, C circling NA northwest of airport between Rwy 8L-26R and 4L-22R. Cat. D, E circling NA north of Rwy 8L-26R.





MISSED APPROACH: Climbing right turn to 3600 direct GECKO and hold.

ATIS 127.9 251.15	HCF APPROACH 118.3 269.0	HONOLULU TOWER 118.1 257.8	GND CON 121.9 348.6	CLNC DEL 121.4 281.4	RAMP CONTROL 121.8
-----------------------------	------------------------------------	---	-------------------------------	--------------------------------	------------------------------



ELEV	13	SEALANES: 8W-26W 5000 X 300 4W-22W 3000 X 150
------	-----------	---



CATEGORY	A	B	C	D	E
LNNAV MDA	460-1/2	447 (500-1/2)	460-3/4 447 (500-3/4)	460-1	447 (500-1)
CIRCLING	620-1	607 (700-1)	620-1 3/4 607 (700-1 3/4)	820-2 1/2 807 (900-2 1/2)	1660-3 1647 (1700-3)


MIRL Rwy 4L-22R
REIL Rwy 4L, 8R, 22L, 22R and 26R
HIRL Rwy 4R-22L, 8L-26R and 8R-26L

RNAV (RNP) RWY 26L




HONOLULU INTL (HNL) (PHNL)

APP CRS	Rwy Idg	12000
259°	TDZE	10
	Apt Elev	13

RF and GPS REQUIRED. For uncompensated Baro-VNAV systems, procedure NA below 15°C (58°F) or above 49°C (121°F).
NA For inoperative MALSF, increase RNP 0.15 visibility to 1 all Cats.
 * Missed approach requires a minimum climb of 234' per NM to 300.

MALSF
 MISSED APPROACH: Climb to 3000 via 259° track to KABTE, left turn via 4.9 radius to LAYIG, 133° track to ALANA and hold.

ATIS	HCF APPROACH	HONOLULU TOWER	GND CON	CLNC DEL	RAMP CONTROL
127.9 251.15	118.3 269.0	118.1 257.8	121.9 348.6	121.4 281.4	121.8



CATEGORY	A	B	C	D
RNP 0.15 DA*	260-1/2		250 (300-1/2)	

MIRL Rwy 4L-22R
 REIL Rwy 4L, 8R, 22L, 22R and 26R
 HIRL Rwy 4R-22L, 8L-26R and 8R-26L

SPECIAL AIRCRAFT & AIRCREW AUTHORIZATION REQUIRED

RNAV (RNP) Z RWY 4R

HONOLULU INTL (HNL) (PHNL)


APP CRS	Rwy Idg	9000
042°	TDZE	9
	Apt Elev	13

V GPS Required. For uncompensated Baro-VNAV systems, procedure NA below 16°C (60°F) or above 48°C (119°F). For inoperative MALSR, increase RNP 0.30 visibility to 2¼.


MALSR


MISSED APPROACH: Climbing right turn to 5000 direct LUYEV and hold.

ATIS 127.9 251.15	HCF APPROACH 118.3 269.0	HONOLULU TOWER 118.1 257.8	GND CON 121.9 348.6	CLNC DEL 121.4 281.4	RAMP CONTROL 121.8
-----------------------------	------------------------------------	---	-------------------------------	--------------------------------	------------------------------



ELEV	13	SEALANES: 8W-26W 5000 X 300 4W-22W 3000 X 150
D		



MIRL Rwy 4L-22R
 REIL Rwys 4L, 8R, 22L, 22R and 26R
 HIRL Rwys 4R-22L, 8L-26R and 8R-26L

	RCHEW	PERLY	RW04R
	2000	1500	
Procedure Turn NA	042°		
GP 3.00° TCH 55	1500		
	6 NM	4.5 NM	
CATEGORY	A	B	C
RNP 0.30 DA	658-1¾ 649 (700-1¾)		

SPECIAL AIRCRAFT & AIRCREW AUTHORIZATION REQUIRED

RNAV (RNP) Z RWY 8L

HONOLULU INTL (HNL) (PHNL)


APP CRS	Rwy Idg	12300
079°	TDZE	13
	Apt Elev	13

GPS REQUIRED. For uncompensated Baro-VNAV systems, procedure NA below 15°C (58°F) or above 49°C (121°F). For inoperative MALSR increase RNP 0.30 visibility to 1¼ all Cats.




MISSED APPROACH: Climb to 700 then climbing right turn to 3000 direct ALANA and hold.

ATIS	HCF APPROACH	HONOLULU TOWER	GND CON	CLNC DEL	RAMP CONTROL
127.9 251.15	118.3 269.0	118.1 257.8	121.9 348.6	121.4 281.4	121.8



ELEV	13	SEALANES:
		8W-26W 5000 X 300
		4W-22W 3000 X 150




VGSIs and RNAV glidepath not coincident.			
HALAU	KAHEA	RWY 08L	
3000	2000	2000	
7.1 NM		5.9 NM	
Procedure Turn NA	GP 3.00° TCH 65		
CATEGORY	A	B	C
RNP 0.30 DA	344-¾		331 (400-¾)

MIRL Rwy 4L-22R
REIL Rws 4L, 8R, 22L, 22R and 26R
HIRL Rws 4R-22L, 8L-26R and 8R-26L

SPECIAL AIRCRAFT & AIRCREW AUTHORIZATION REQUIRED

HCF APPROACH
 118.3 269.0
 ATIS
 127.9 251.15



(NARRATIVE ON FOLLOWING PAGE)

NOTE: Chart not to scale.

SAKKI FOUR ARRIVAL (SAKKI.SAKKI4)

ARRIVAL DESCRIPTION

CHAIN TRANSITION (CHAIN.SAKKI4): From over CHAIN INT via LNY 13 DME Arc to intercept LNY R-278 to SAKKI INT. Thence....

DOVRR TRANSITION (DOVRR.SAKKI4): From over DOVRR INT via MKK R-180 to JORDA INT, left turn heading 315° to join I-EPC LDA course at 40 DME to SAKKI INT. Thence....

FIRES TRANSITION (FIRES.SAKKI4): From over FIRES INT via HNL R-125 to JORDA INT, right turn heading 315° to join I-EPC LDA course at 40 DME to SAKKI INT. Thence....

LANAI TRANSITION (LNY.SAKKI4): From over LNY VORTAC via LNY R-278 to SAKKI INT. Thence....

UPOLU TRANSITION (UPP.SAKKI4): From over UPP VORTAC via UPP R-272 and HNL R-125 to JORDA INT, right turn heading 315° to join I-EPC LDA course at 40 DME to SAKKI INT. Thence....

....For Runways 22/26 only: From over SAKKI INT via the LDA/DME Runway 26L course to SECIL DME.




VOR/DME or TACAN or GPS-B HONOLULU INTL (HNL) (PHNL)

VORTAC HNL 114.8 Chan 95	APP CRS 037°	Rwy Idg TDZE Apt Elev 13	N/A N/A 13
--	------------------------	--	------------------

⚠ Cat. A, B, C circling not authorized northwest of airport between Rwy 8L-26R and 4L-22R. Cat. D circling not authorized north of Rwy 8L-26R. Cat. E circling not authorized north of Rwy 8R-26L.

MISSED APPROACH: Climbing right turn to 3000 via HNL R-171 to ALANA/HNL 13.9 DME and hold.

ATIS 127.9 251.15	HCF APPROACH 118.3 269.0	HONOLULU TOWER 118.1 257.8	GND CON 121.9 348.6	CLNC DEL 121.4 281.4	RAMP CONTROL 121.8
-----------------------------	------------------------------------	--------------------------------------	-------------------------------	--------------------------------	------------------------------



CATEGORY	A	B	C	D	E
CIRCLING	620-1 607 (700-1)		620-1 ³ / ₄ 607 (700-1 ³ / ₄)	760-2 ¹ / ₂ 747 (800-2 ¹ / ₂)	860-3 847 (900-3)

MIRL Rwy 4L-22R
REIL Rwy 4L, 8R, 22L, 22R and 26R
HIRL Rwy 4R-22L, 8L-26R and 8R-26L


VOR or TACAN or GPS-A HONOLULU INTL (HNL)(PHNL)

VORTAC HNL 114.8 Chan 95	APP CRS 305°	Rwy Idg TDZE Apt Elev	N/A N/A 13
--	------------------------	-----------------------------	-------------------------




⚠ Cat. A, B, C circling not authorized northwest of airport between Rwys 8L-26R and 4L-22R; Cat. D, E circling not authorized north of Rwy 8L-26R.

MISSED APPROACH: Climbing left turn to 3000 via HNL R-171 to ALANA Int/HNL 13.9 DME and hold.

ATIS 127.9 251.15	HCF APPROACH 118.3 269.0	HONOLULU TOWER 118.1 257.8	GND CON 121.9 348.6	CLNC DEL 121.4 281.4	RAMP CONTROL 121.8
-----------------------------	------------------------------------	--------------------------------------	-------------------------------	--------------------------------	------------------------------



ELEV 13	SEALANES: 8W-26W 5000 X 300 4W-22W 3000 X 150
----------------	---



MIRL Rwy 4L-22R
REIL Rwys 4L, 8R, 22L, 22R and 26R
HIRL Rwys 4R-22L, 8L-26R and 8R-26L

CATEGORY	A	B	C	D	E
CIRCLING	620-1	607 (700-1)	620-1 ³ / ₄ 607 (700-1 ³ / ₄)	760-2 ¹ / ₂ 747 (800-2 ¹ / ₂)	1500-3 1487 (1500-3)

VOR or TACAN RWY 4R

HONOLULU INTL (HNL) (PHNL)




VORTAC HNL 114.8 Chan 95	APP CRS 018°	Rwy Idg TDZE Apt Elev 9000 9 13
--	------------------------	---

▼ ▲ Cat. A, B, C circling not authorized northwest of airport between Rwy 8L-26R and 4L-22R. Cat. D circling not authorized north of Rwy 8L-26R. Inoperative table does not apply.


MALSR

MISSED APPROACH: Climbing right turn to 3000 via HNL R-171 to ALANA Int/HNL 13.9 DME and hold.

ATIS 127.9 251.15	HCF APPROACH 118.3 269.0	HONOLULU TOWER 118.1 257.8	GND CON 121.9 348.6	CLNC DEL 121.4 281.4	RAMP CONTROL 121.8
-----------------------------	------------------------------------	--------------------------------------	-------------------------------	--------------------------------	------------------------------



ELEV 13	SEALANES: 8W-26W 5000 X 300 4W-22W 3000 X 150
---------	---



CATEGORY	A	B	C	D
S-4R	460-1	451 (500-1)	460-1½ 451 (500-1¼)	460-1½ 451 (500-1½)
CIRCLING	620-1	607 (700-1)	620-1¾ 607 (700-1¾)	760-2½ 747 (800-2½)

MIRL Rwy 4L-22R
REIL Rwy 4L, 8R, 22L, 22R and 26R
HNL Rwy 4R-22L, 8L-26R and 8R-26L

FAF to MAP 3.9 NM

Knots	60	90	120	150	180
Min:Sec	3:54	2:36	1:57	1:34	1:18

AIRPORT DIAGRAM

AL-762 (FAA)


KAHALUI (OGG)(PHOG)
KAHALUI, HAWAII

ATIS
128.6
MAUI TOWER ★
118.7 279.6
GND CON
121.9 279.6
CLNC DEL
120.6 290.5

CAUTION: BE ALERT TO RUNWAY CROSSING CLEARANCES.
READBACK OF ALL RUNWAY HOLDING INSTRUCTIONS IS REQUIRED.



JANUARY 2005
ANNUAL RATE OF CHANGE
0.0° W



PAC. 08 APR 2010 to 03 JUN 2010

RWY 2-20
S130, D170, DT360, DDT750
RWY 5-23
S130, D170, DT270


156° 26.5' W 156° 26.0' W 156° 25.5' W

BARBY ONE DEPARTURE

ATIS 128.6
 CLNC DEL
 120.6 290.5
 GND CON
 121.9 279.6
 MAUI TOWER *
 118.7 (CTAF) 279.6
 MAUI DEP CON
 NORTH 120.2 322.4
 SOUTH 119.5 225.4
 HCF APPROACH
 NORTH 120.2 322.4
 SOUTH 119.5 225.4

TAKE-OFF MINIMUMS:

Rwy 23: NA Obstacle and ATC.
 Rwy 2: Standard with ATC climb of 480 feet per NM to 2200.
 Rwy 5: Standard with ATC climb of 480 feet per NM to 2900.
 Rwy 20: Standard with minimum climb of 480 feet per NM to 2100.



NOTE: Chart not to scale.



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 2: Climb heading 024° to 2100 then climbing right turn to 7000 via heading 115° to intercept OGG VORTAC R-085 (V15-22) to BARBY INT/OGG 25 DME.

TAKEOFF RUNWAY 5: Climbing left turn heading 024° to 2100 then climbing right turn to 7000 via heading 115° to intercept OGG VORTAC R-085 (V15-22) to BARBY INT/OGG 25 DME.

TAKEOFF RUNWAY 20: Climb heading 204° to 2100 then climbing left turn to 7000 direct OGG VORTAC then via OGG R-085 (V15-22) to BARBY INT OGG 25 DME.

TAKEOFF OBSTACLE NOTES:

Rwy 2: Bush/trees beginning 190 feet from DER, 362 feet left of centerline, up to 60 feet AGL/79 feet MSL. Pipe on building 339 feet from DER, 289 feet right of centerline, 20 feet AGL/25 feet MSL. Bush beginning 902 feet from DER, 637 feet right of centerline, up to 20 feet AGL/39 feet MSL.


Rwy 5: Trees 2,359 feet from DER, 512 feet left of centerline, 56 feet AGL/75 feet MSL. Fence beginning 20 feet from DER, 299 feet right of centerline, up to 7 feet AGL/31 feet MSL. Bush/trees beginning 291 feet from DER, 300 feet right of centerline, up to 76 feet AGL/95 feet MSL.

Rwy 20: Bush 22 feet from DER, 236 feet right of centerline, 2 feet AGL/55 feet MSL. Bush/trees beginning 24 feet from DER, 173 feet left of centerline, up to 29 feet AGL/68 feet MSL.

PAC: 08 APR 2010 to 03 JUN 2010

BEACH TWO DEPARTURE

ATIS 128.6
 CLNC DEL
 120.6 290.5
 GND CON
 121.9 279.6
 MAUI TOWER ★
 118.7 (CTAF) 279.6
 HCF APPROACH
 119.5 225.4



DEPARTURE ROUTE DESCRIPTION

TAKE-OFF RUNWAYS 2, 5, AND 23: Maintain flight in visual conditions until intercepting the OGG R-195, then climb southbound via the OGG R-195 to BEACH INT.


TAKE-OFF RUNWAY 20: Turn left to intercept the OGG R-195, then climb southbound via the OGG R-195 to BEACH INT.

HARPO TRANSITION (BEACH2.HARPO): Cross BEACH INT at or above 5500', turn left, continue to climb southbound via IAI R-324 to intercept V2 at or above 7000'.

LANAI TRANSITION (BEACH2.LNY): Cross BEACH INT at or above 4000', turn right, continue climb to 5000' or above via LNY R-090 to LNY VORTAC.

CAMPS TWO ARRIVAL (CAMPS.CAMPS2)

ATIS
128.6
HCF APPROACH
119.5 343.8
MAUI TOWER ★
118.7 279.6



NOTE: Chart not to scale.

LANAI TRANSITION (LNY.CAMPS2): From over LNY VORTAC via LNY R-095 to CAMPS INT. Thence

MAKEN TRANSITION (MAKEN.CAMPS2): From over MAKEN INT via UPP R-294 and LNY R-095 to CAMPS INT. Thence

. . . . From over CAMPS INT via I-OGG localizer course to KAHULUI AIRPORT.

LOC/DME I-OGG 110.1 Chan 38	APP CRS 024°	Rwy Idg TDZE Apt Elev	6995 54 54
---	------------------------	-----------------------------	---------------------------------------

ILS or LOC RWY 2

KAHALUI (OGG)(PHOG)



⚠ Inoperative table does not apply to ILS all Cats, LOC Cat A and B. DME or RADAR required. Visibility reduction by helicopters NA. For inoperative MALSR, increase NOWAK fix minimums LOC Cat A and B visibility ½ mile, increase Cat E ½ mile.

MALSR



MISSED APPROACH: Climb to 3000 via OGG R-024 then climbing right turn to 5000 direct OGG VORTAC, then via OGG R-190 and LNY R-095 to CAMPS and hold.

ATIS 128.6	HCF APPROACH 120.2 322.4 (NORTH) 119.5 225.4 (SOUTH)	MAUI TOWER★ 118.7 (CTAF) 0 279.6	GND CON 121.9 279.6	CLNC DEL 120.6 290.5	UNICOM 122.95
----------------------	--	--	-------------------------------	--------------------------------	-------------------------



Use I-OGG DME when on the localizer course.

3000	5000	OGG	OGG R-190	CAMPS
↑	↘	115.1	OGG R-190 & LNY R-095	△
OGG R-024				

One Minute Holding Pattern

CAMPS I-OGG (17.5)

TEBBS I-OGG (10) RADAR

VGS1 and ILS glidepath not coincident.

NOWAK I-OGG (5.5) RADAR

*LOC only

I-OGG (2.4) I-OGG (1.1)

CATEGORY	A	B	C	D	E
S-ILS 2	304-¾ 250 (300-¾)				
S-LOC 2	1520-1¼ 1466 (1500-1¼)	1520-1½ 1466 (1500-1½)	1520-2½	1466 (1500-2½)	
CIRCLING	1520-1¼ 1466 (1500-1¼)	1520-1½ 1466 (1500-1½)	1520-3	1466 (1500-3)	

NOWAK FIX MINIMUMS

S-LOC 2	520-¾ 466 (500-¾)	520-1 466 (500-1)	520-1¼ 466 (500-1¼)
---------	-------------------	----------------------	------------------------

HIRL Rwy 2-20
MIRL Rwy 5-23

FAF to MAP 8.8 NM

Knots	60	90	120	150	180
Min:Sec	8:48	5:52	4:24	3:31	2:56

CIRCLING	520-1 466 (500-1)	560-1 506 (600-1)	620-1½ 566 (600-1½)	660-2 606 (700-2)	1400-3 1346 (1400-3)
----------	----------------------	----------------------	------------------------	----------------------	-------------------------

LOC/DME I-OGG 110.1 Chan 38	APP CRS 204°	Rwy Idg TDZE Apt Elev 6995 25 54
---	------------------------	--




LOC/DME BC RWY 20

KAHALUI (OGG)(PHOG)

DME required.

MISSED APPROACH: Climb to 6000 via OGG R-190 and LNY VORTAC R-090 to DIPPS INT and hold.

ATIS 128.6	HCF APPROACH 120.2 322.4 (NORTH) 119.5 225.4 (SOUTH)	MAUI TOWER ★ 118.7 (CTAF) 0 279.6	GND CON 121.9 279.6	CLNC DEL 120.6 290.5	UNICOM 122.95
----------------------	--	---	-------------------------------	--------------------------------	-------------------------




CATEGORY	A	B	C	D	E
S-20	460-1	435 (500-1)	460-1¼ 435 (500-1¼)	460-1½	435 (500-1½)
CIRCLING	500-1 446 (500-1)	560-1 506 (600-1)	620-1½ 566 (600-1½)	660-2 606 (700-2)	1400-3 1346 (1400-3)

HIRL Rwy 2-20
MIRL Rwy 5-23

PAC. 08 APR 2010 to 03 JUN 2010

MAUI FIVE DEPARTURE

ATIS 128.6
CLNC DEL
120.6 290.5
GND CON
121.9 279.6
MAUI TOWER ★
118.7 (CTAF) 279.6
HCF APPROACH
120.2 322.4



PAC: 08 APR 2010 to 03 JUN 2010

DEPARTURE ROUTE DESCRIPTION

TAKE-OFF RUNWAYS 2 AND 5 ONLY: After take-off, all aircraft fly heading 360°, expect radar vectors west of Maui Island to assigned fix/route. Cross the LNY R-322 at assigned altitude. When assigned above 14,000', cross at or above 14,000'.

LOST COMMUNICATIONS: If not in contact with Departure Control 1 minute after crossing the shoreline, climb northbound via the OGG R-010 until reaching at least 3500'. Then reverse course to the right direct OGG VORTAC. Then via V24 to LNY VORTAC. Cross OGG VORTAC at or above 6700'.

NDB/DME RWY 2




KAHALUI (OGG)(PHOG)

NDB VYI <u>327</u>	APP CRS 005°	Rwy Idg TDZE Apt Elev	6995 54 54
------------------------------	------------------------	-----------------------------	---------------------------------------


MALS
AS

MISSED APPROACH: Climb to 4000 via 005° bearing from VYI NDB then climb to 7000 direct VYI NDB and hold.

ATIS 128.6	HCF APPROACH 120.2 322.4 (NORTH) 119.5 225.4 (SOUTH)	MAUI TOWER ★ 118.7 (CTAF) 279.6	GND CON 121.9 279.6	CLNC DEL 120.6 290.5	UNICOM 122.95
----------------------	--	---	-------------------------------	--------------------------------	-------------------------



CATEGORY	A	B	C	D
S-2	640-3/4 586 (600-3/4)		640-1 1/2 586 (600-1 1/2)	640-1 3/4 586 (600-1 3/4)
CIRCLING	640-1 586 (600-1)		640-1 1/2 586 (600-1 1/2)	640-2 586 (600-2)



HIRL Rwy 2-20
MIRL Rwy 5-23





RNAV (GPS) RWY 2 KAHALUI (OGG)(PHOG)

APP CRS	Rwy Idg	6995
021°	TDZE	54
	Apt Elev	54

NA Circling NA at night to Rwy 5.
GPS or RNP-0.3 Required. DME/DME RNP-0.3 NA.
For inoperative MALSR increase LNAV visibility ¼ mile.

MALSR MISSED APPROACH: Climb to 2700 then climbing right turn to 6000 direct HARPO WP and hold.

ATIS 128.6	HCF APPROACH 120.2 322.4 (NORTH) 119.5 225.4 (SOUTH)	MAUI TOWER ★ 118.7 (CTAF) 279.6	GND CON 121.9 279.6	CLNC DEL 120.6 290.5	UNICOM 122.95
----------------------	--	---	-------------------------------	--------------------------------	-------------------------



CATEGORY	A	B	C	D
LNAV MDA	400-¾ 346 (400-¾)			400-1 346 (400-1)
CIRCLING	500-1 446 (500-1)	560-1 506 (600-1)	620-1½ 566 (600-1½)	640-2 586 (600-2)

HIRL Rwy 2-20
MIRL Rwy 5-23

RNAV (GPS) RWY 20




KAHALUI (OGG)(PHOG)

APP CRS	Rwy Idg	6995
204°	TDZE	25
	Apt Elev	54

GPS or RNP-0.3 Required.
DME/DME RNP-0.3 NA.

MISSED APPROACH: Climbing left turn to 6000 direct HARPO WP and hold.

ATIS 128.6	HCF APPROACH 120.2 322.4 (NORTH) 119.5 225.4 (SOUTH)	MAUI TOWER ★ 118.7 (CTAF) 279.6	GND CON 121.9 279.6	CLNC DEL 120.6 290.5	UNICOM 122.95
----------------------	--	---	-------------------------------	--------------------------------	-------------------------



CATEGORY	A	B	C	D
RNAV MDA	400-1 375 (400-1)		400-1¼ 375 (400-1¼)	
CIRCLING	660-1 606 (700-1)	720-1 666 (700-1)	780-2 726 (800-2)	800-2½ 746 (800-2½)

HIRL Rwy 2-20
 MIRL Rwy 5-23

RNAV (GPS) RWY 23

KAHALUI (OGG)(PHOG)





APP CRS	Rwy Idg	4990
234°	TDZE	17
	Apt Elev	54

▼ DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA.
▲ When local altimeter setting not received, procedure NA.
 Straight-in minimums NA at night.

MISSED APPROACH: Climbing right turn to 4000 direct ZULUD and hold, continue climb-in-hold to 4000.

ATIS 128.6	HCF APPROACH 120.2 322.4 (NORTH) 119.5 225.4 (SOUTH)	MAUI TOWER ★ 118.7 (CTAF) 0 279.6	GND CON 121.9 279.6	CLNC DEL 120.6 290.5	UNICOM 122.95
----------------------	--	---	-------------------------------	--------------------------------	-------------------------

Procedure NA for arrivals at PLUMB via V6-22 northwest bound.




CATEGORY	A	B	C	D
LNNAV MDA	460-1	443 (500-1)	460-1¼ 443 (500-1¼)	460-1½ 443 (500-1½)
CIRCLING	520-1 466 (500-1)	560-1 506 (600-1)	620-1½ 566 (600-1½)	640-2 586 (600-2)

HIRL Rwy 2-20
 MIRL Rwy 5-23

SMOKE STACK VISUAL RWY 2

KAHULUI (OGG PHOG)
KAHULUI, HAWAII



ATIS 128.6
HCF APPROACH
119.5 225.4
MAUI TOWER ★
118.7 279.6

RADAR REQUIRED

Weather minima: Ceiling 3000 feet. Visibility 3 miles.

PROCEDURE NOT AUTHORIZED AT NIGHT.

Chart not to scale.

Vertical Guidance Navaid and Angle:
I-OGG LOC (GS 3.00°)

LANAI
117.7 LNY
Chan 124

MAUI
115.1 OGG
Chan 98

LOCALIZER 110.1
I-OGG

VALLEY ISLAND
327 VVI

290
KNUJI TOWER

When visual approaches to RWY 2 are in progress, arriving aircraft may be cleared for a "Smoke Stack Visual Runway 2 Approach". Aircraft inbound via:
LANAI: Proceed to mid-Maalaea Bay via a route on or south of the LNY VORTAC R-085, thence direct to the KNUJI Radio Tower, thence....
MAKENA: Proceed to the KNUJI Radio Tower, thence....
....intercept the RWY 2 extended centerline at or prior to the Sugar Mill Smoke Stacks and proceed to the airport.

SWEEP ONE DEPARTURE


ATIS 128.6
CLNC DEL
120.6 290.5
GND CON
121.9 279.6
MAUI TOWER *
118.7 (CTAF) 279.6
MAUI DEP CON
NORTH 120.2 322.4
SOUTH 119.5 225.4
HCF APPROACH
NORTH 120.2 322.4
SOUTH 119.5 225.4

TAKE-OFF MINIMUMS:

Rwy 23: NA Obstacle and ATC.

Rwy 2,5: Standard with ATC climb of 480 feet per NM to 2100.

Rwy 20: Standard with minimum climb of 480 feet per NM to 2100.



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 2: Climb heading 024° to 2100 then climbing right turn to 6000 via heading 095° to intercept OGG VORTAC R-069 (V11) to SWEEP INT/OGG 24 DME.

TAKEOFF RUNWAY 5: Climb heading 024° to 2100 then right turn to 6000 via heading 095° to intercept OGG VORTAC R-069 (V11) to SWEEP INT/OGG 24 DME.

TAKEOFF RUNWAY 20: Climb heading 204° to 2100 then climbing left turn to 6000 direct OGG VORTAC then via OGG R-069 (V11) to SWEEP INT/OGG 24 DME.

TAKEOFF OBSTACLE NOTES:

Rwy 2: Bush/trees beginning 190 feet from DER, 362 feet left of centerline, up to 60 feet AGL/79 feet MSL. Pipe on building 339 feet from DER, 289 feet right of centerline, 20 feet AGL/25 feet MSL. Bush beginning 902 feet from DER, 637 feet right of centerline, up to 20 feet AGL/39 feet MSL.

Rwy 5: Trees 2,359 feet from DER, 512 feet left of centerline, 56 feet AGL/75 feet MSL. Fence beginning 20 feet from DER, 299 feet right of centerline, up to 7 feet AGL/31 feet MSL. Bush/trees beginning 291 feet from DER, 300 feet right of centerline, up to 76 feet AGL/95 feet MSL.

Rwy 20: Bush 22 feet from DER, 236 feet right of centerline, 2 feet AGL/55 feet MSL. Bush/trees beginning 24 feet from DER, 173 feet left of centerline, up to 29 feet AGL/68 feet MSL.

VOR/DME or TACAN RWY 20



KAHALUI (OGG)(PHOG)

VORTAC OGG	APP CRS	Rwy Idg	6995
115.1	194°	TDZE	25
Chan 98		Apt Elev	54

▼ When tower closed, procedure not authorized except for operators with approved weather reporting service.

MISSED APPROACH: Climb to 6000 via OGG VORTAC R-187 to intercept LNY R-090, then climbing right turn direct DIPPSS Int and hold.

ATIS	HCF APPROACH	MAUI TOWER ★	GND CON	CLNC DEL	UNICOM
128.6	120.2 322.4 (NORTH) 119.5 225.4 (SOUTH)	118.7 (CTAF) 0 279.6	121.9 279.6	120.6 290.5	122.95



6000	LNY R-090	DIPPSS	MIKEY OGG 5	Remain within 10 NM
OGG R-187 115.1				
VORTAC				
0.2	5 NM			

CATEGORY	A	B	C	D
S-20	400-1 375 (400-1)			400-1¼ 375 (400-1¼)
CIRCLING	520-1 466 (500-1)	560-1 506 (600-1)	620-1½ 566 (600-1½)	640-2 586 (600-2)

HIRL Rwy 2-20


MIRL Rwy 5-23

VOR RWY 20 KAHALUI (OGG)(PHOG)

VORTAC OGG 115.1 Chan 98	APP CRS 194°	Rwy Idg TDZE Apt Elev	6995 25 54
--	------------------------	-----------------------------	---------------------------------------

MISSED APPROACH: Climb to 6000 via OGG R-187 to intercept LNY R-090, then climbing right turn direct DIPP'S Int and hold.

ATIS 128.6	HCF APPROACH 120.2 322.4 (NORTH) 119.5 225.4 (SOUTH)	MAUI TOWER ★ 118.7 (CTAF) 0 279.6	GND CON 121.9 279.6	CLNC DEL 120.6 290.5	UNICOM 122.95
----------------------	--	---	-------------------------------	--------------------------------	-------------------------



6000
↑
OGG R-187
115.1

LNY R-090

DIPP'S

*VORTAC

Remain within 10 NM


014°

1900

194°

*Maintain 4500 or above until established outbound for procedure turn. Maximum procedure turn entry altitude 6500.

0.2



CATEGORY	A	B	C	D
S-20	420-1	395 (400-1)		420-1½ 395 (400-1½)
CIRCLING	520-1 466 (500-1)	560-1 506 (600-1)	620-1½ 566 (600-1½)	640-2 586 (700-2)

HIRL Rwy 2-20
MIRL Rwy 5-23

AIRPORT DIAGRAM

KAILUA-KONA/ KONA INTL AT KEAHOLE (KOA) (PHKO)
AL-5761 (FAA) KAILUA-KONA, HAWAII

ATIS 127.4
KONA TOWER★
120.3 (CTAF) 254.3
CLNC DEL
121.9

400 X 150

FIELD
ELEV
47

175.0°

19°45'N

Areas not visible from control tower

VAR 9.0°E

JANUARY 2005
ANNUAL RATE OF CHANGE
0.0°W

INTERNATIONAL
ARRIVALS

11000 X 150

▲ 194 ±

19°44'N

TERMINAL

CONTROL TOWER

FIRE STATION

AIR CARGO

COMMUTER
TERMINAL

RWY 17-35
S75, D200, ST175, DT400, DDT850

BRAVO S

RAMP K

FUEL FARM TANKS

SOUTH RAMP

ELEV
38

35

400 X 150

CAUTION: BE ALERT TO RUNWAY CROSSING CLEARANCES.
READBACK OF ALL RUNWAY HOLDING INSTRUCTIONS IS REQUIRED.

156°03'W

156°02'W


PAC. 08 APR 2010 to 03 JUN 2010


AMERY TWO DEPARTURE


SL-5761 (FAA)

KAILUA-KONA, HAWAII

ATIS 127.4
 CLNC DEL
 121.9
 KONA TOWER*
 120.3 (CTAF) 254.3
 HCF APPROACH
 126.0 278.3

MAUI
 115.1 OGG 
 Chan 98

UPOLU POINT
 112.3 UPP 
 Chan 70



NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKE-OFF RUNWAY 17: Climb on runway heading to 500 ft., then climbing right turn to heading 270°, intercept IAI R-297 to AMERY INT. Thence via (transition).

TAKE-OFF RUNWAY 35: Climb on runway heading to 500 ft., then climbing left turn to heading 270°, intercept IAI R-297 to AMERY INT. Thence via (transition).

ROWIN TRANSITION (AMERY2.ROWIN): From AMERY INT via OGG R-169 to ROWIN INT.

TYPHO TRANSITION (AMERY2.TYPHO): From AMERY INT via IAI R-297 to TYPHO INT.

PAC. 08 APR 2010 to 03 JUN 2010

LOC/DME I-KOA 109.7 Chan 34	APP CRS 174°	Rwy Idg 11000 TDZE 47 Apt Elev 47
---	------------------------	--

ILS or LOC/DME RWY 17



KAILUA-KONA/ KONA INTL AT KEAHOLE (KOA)(PHKO)

▲ For inoperative MALS, increase S-ILS Rwy 17 Cat E visibility to $\frac{3}{4}$, and S-LOC 17 Cat E visibility to $\frac{1}{4}$.
▲ Circling NA east of Rwy 17-35.
Autopilot coupled approach NA below 415.




MISSED APPROACH: Climb to 500 then climbing right turn to 5000 via IAI VORTAC R-297 to ANDES INT/IAI 15 DME and hold, continue climb-in-hold to 5000.

ATIS 127.4	HCF APPROACH 126.0 278.3	KONA TOWER ★ 120.3(CTAF) 254.3	CLNC DEL 121.9
----------------------	------------------------------------	--	--------------------------




CATEGORY	A	B	C	D	E
S-ILS 17	247- $\frac{1}{2}$ 200 (200- $\frac{1}{2}$)				
S-LOC 17	400- $\frac{1}{2}$ 353 (400- $\frac{1}{2}$)				
CIRCLING	460-1 413 (500-1)	500-1 453 (500-1)	500-1 $\frac{1}{2}$ 453 (500-1 $\frac{1}{2}$)	600-2	553 (600-2)



KAYAK FOUR ARRIVAL

ST-5761 (FAA) KONA INTL AT KEAHOE (KOA) (KOA) (PHKO) KAILUA-KONA, HAWAII



NOTE: DME Required
NOTE: Chart not to scale.

PAC: 08 APR 2010 to 03 JUN 2010

(NARRATIVE ON FOLLOWING PAGE)

ARRIVAL DESCRIPTION

BARBY TRANSITION (BARBY.KAYAK4): From over BARBY INT via IAI R-351, UPP R-212 and IAI R-339 to KAYAK INT. Thence....

FIRES TRANSITION (FIRES.KAYAK4): From over FIRES INT via MUE R-274, LNY R-119 and IAI R-339 to KAYAK INT. Thence....

HEFTI TRANSITION (HEFTI.KAYAK4): From over HEFTI INT via LNY R-119 and IAI R-339 to KAYAK INT. Thence....

LANAI TRANSITION (LNY.KAYAK4): From over LNY VORTAC via LNY R-119 and IAI R-339 to KAYAK INT. Thence....

MOLOKAI TRANSITION (MKK.KAYAK4): From over MKK VORTAC via MKK R-108 and IAI R-339 to KAYAK INT. Thence....

OKALA TRANSITION (OKALA.KAYAK4): From over OKALA INT via MUE R-077 to MUE VOR/DME. Then via MUE R-245 to KAYAK INT. Thence....

UPOLU TRANSITION (UPP.KAYAK4): From over UPP VORTAC via UPP R-212 and IAI R-339 to KAYAK INT. Thence....

....From over KAYAK INT via IAI R-339 to BILGE DME.

LOC BC RWY 35

KAILUA-KONA/KONA INTL AT KEAHOLE (KOA) (PHKO)

LOC/DME I-KOA 109.7 Chan 34	APP CRS 354°	Rwy Idg 11000 TDZE 37 Apt Elev 47
---	------------------------	--

Circling NA east of Rwy 17-35.

MISSED APPROACH: Climbing left turn to 5000 via IAI R-297 to ANDES INT/IAI 15 DME and hold, continue climb-in-hold to 5000.


ATIS
127.4

HCF APPROACH
126.0 278.3

KONA TOWER *
120.3 (CTAF) 254.3

CLNC DEL
121.9

BACK COURSE




Use I-KOA DME when on LOC course.
Remain within 10 NM

*HOXLY INT I-KOA **4.8**


5000 ANDES IAI R-297

VGSI and descent angles not coincident. Disregard glide slope indications.



*Maintain 4500 feet or above until established outbound for procedure turn.

JENSO I-KOA **0.5**



CATEGORY	A	B	C	D
S-35		400-1 363 (400-1)		400-1½ 363 (400-1½)
CIRCLING	460-1 413 (500-1)	500-1 453 (500-1)	500-1½ 453 (500-1½)	600-2 553 (600-2)

FAF to MAP 4.3 NM					
Knots	60	90	120	150	180
Min:Sec	4:18	2:52	2:09	1:43	1:26

RNAV (GPS) RWY 17

KAILUA-KONA/ KONA INTL AT KEAHOLE (KOA) (PHKO)

APP CRS	Rwy Idg	11000
174°	TDZE	47
	Apt Elev	47




NA Baro-VNAV NA below -5°C (23°F).
GPS or RNP-0.3 required. DME/DME RNP-0.3 NA.
Circling NA east of Rwy 17-35.
WAAS VNAV NA.

MALSRL



MISSED APPROACH: Climb to 5000 direct HOXLY WP and via 264° track to HELUT WP and via 354° track to ANDES WP and hold.

ATIS 127.4	HCF APPROACH 126.0 278.3	KONA TOWER * 120.3 (CTAF) 254.3	CLNC DEL 121.9
----------------------	------------------------------------	---	--------------------------



CATEGORY	A	B	C	D
GLS PA DA	NA			
LNAV/VNAV DA	540-1¼ 493 (500-1¼)			
LNAV MDA	640-½ 593 (600-½)	640-1 593 (600-1)	640-1¼ 593 (600-1¼)	
CIRCLING	640-1¾ 593 (600-1¾)			640-2 593 (600-2)

HIRL Rwy 17-35

RNAV (GPS) Y RWY 35





KAILUA-KONA/ KONA INTL AT KEAHOLE (KOA) (PHKO)

APP CRS	Rwy Idg	11000
354°	TDZE	37
	Apt Elev	47

NA Circling NA east of Rwy 17-35.
GPS or RNP-0.3 required.
DME/DME RNP-0.3 NA.

MISSED APPROACH: Climbing left turn to 5000 direct ANDES WP and hold.

ATIS 127.4	HCF APPROACH 126.0 278.3	KONA TOWER ★ 120.3 (CTAF) 0 254.3	CLNC DEL 121.9
----------------------	------------------------------------	---	--------------------------



CATEGORY	A	B	C	D	E
LNAV MDA	400-1 363 (400-1)		400-1¼ 363 (400-1¼)		
CIRCLING	460-1 413 (500-1)	500-1 453 (500-1)	500-1½ 453 (500-1½)	600-2	553 (600-2)

RNAV (GPS) Z RWY 35



KAILUA-KONA/KONA INTL AT KEAHOLE (KOA) (PHKO)

APP CRS	Rwy Idg	11000
354°	TDZE	37
	Apt Elev	47


NA Circling NA east of Rwy 17-35.
Baro-VNAV NA below -5°C (23°F).
GPS or RNP-0.3 required. DME/DME RNP-0.3 NA.
WAAS VNAV NA.

MISSED APPROACH: Climb to 5000 direct EGIPT WP and left turn via 254° track to ANDES WP and hold.


ATIS 127.4	HCF APPROACH 126.0 278.3	KONA TOWER * 120.3 (CTAF) 254.3	CLNC DEL 121.9
----------------------	------------------------------------	---	--------------------------



ELEV 47	HIRL Rwy 17-35
----------------	----------------




CATEGORY	A	B	C	D	E
GLS PA DA	NA				
LNAV/VNAV DA	540-1¾ 503 (500-1¾)				
LNAV MDA	640-1 603 (600-1)	640-1¾ 603 (600-1¾)	640-2 603 (600-2)	640-2¼ 603 (600-2¼)	
CIRCLING	640-1¾ 593 (600-1¾)		593 (600-2)	640-2¼ 593 (600-2¼)	



VECKI SIX ARRIVAL

KAILUA-KONA / KONA INTL AT KEAHOLE (KOA) (PHKO)
ST-5761 (FAA) KAILUA-KONA, HAWAII



(NARRATIVE ON FOLLOWING PAGE)

PAC. 08 APR 2010 to 03 JUN 2010

NOTE: DME Required.
NOTE: Chart not to scale.

ARRIVAL DESCRIPTION

BARBY TRANSITION (BARBY.VECKI6): From over BARBY INT via IAI R-351 and I-KOA localizer course to VECKI INT. Thence....

LANAI TRANSITION (LNY.VECKI6): From over LNY VORTAC via LNY R-119 and I-KOA localizer course to VECKI INT. Thence....

MOLOKAI TRANSITION (MKK.VECKI6): From over MKK VORTAC via MKK R-108, IAI VORTAC R-339, LNY R-119 and I-KOA localizer course to VECKI INT. Thence....

OKALA TRANSITION (OKALA.VECKI6): From over OKALA INT via MUE VOR/DME R-077 to MUE VOR/DME. Thence from over MUE VOR/DME via MUE R-245 to VECKI INT. Thence....

UPOLU TRANSITION (UPP.VECKI6): From over UPP VORTAC via UPP R-209 and I-KOA localizer course to VECKI INT. Thence....


....From over VECKI INT via I-KOA localizer course to KEAHOLE-KONA INTL AIRPORT.

VOR/DME or TACAN RWY 17




KAILUA-KONA/ KONA INTL AT KEAHOLE (KOA) (PHKO)

VORTAC IAI 115.7 Chan 104	APP CRS 159°	Rwy Idg 11000 TDZE 47 Apt Elev 47
---	------------------------	--

⚠ Circling NA east of Rwy 17-35.
Procedure turn NA Cat E aircraft.
Inoperative table does not apply.

MALSR  MISSED APPROACH: Climbing right turn to 1500 via IAI R-297 to ANDES INT/IAI 15 DME and hold.

ATIS 127.4	HCF APPROACH 126.0 278.3	KONA TOWER* 120.3 (CTAF) 254.3	CLNC DEL 121.9
----------------------	------------------------------------	--	--------------------------



CATEGORY	A	B	C	D	E
S-17	600-1 553 (600-1)	600-1½ 553 (600-1½)	600-1¾ 553 (600-1¾)	600-2 553 (600-2)	600-2 553 (600-2)
CIRCLING	600-1 553 (600-1)	600-1½ 553 (600-1½)	600-2 553 (600-2)	600-2 553 (600-2)	600-2 553 (600-2)

VOR or TACAN RWY 35

KAILUA-KONA/ KONA INTL AT KEAHOLE (KOA) (PHKO)

VORTAC IAI	APP CRS	Rwy Idg	11000
115.7	330°	TDZE	37
Chan 104		Apt Elev	47

Circling NA east of Rwy 17-35.
Procedure turn NA for Cat E aircraft.





MISSED APPROACH: Climbing left turn to 1500 via IAI R-297 to ANDES INT/IAI 15 DME and hold.

ATIS
127.4

HCF APPROACH
126.0 278.3

KONA TOWER★
120.3 (CTAF) 254.3

CLNC DEL
121.9



CATEGORY	A	B	C	D	E
S-35	560-1	523 (600-1)	560-1½ 523 (600-1½)	560-1¾	523 (600-1¾)
CIRCLING	560-1	513 (600-1)	560-1½ 513 (600-1½)	600-2	553 (600-2)

RNAV (GPS) RWY 4

KAMUELA/ WAIMEA-KOHALA (MUE) (PHMU)


APP CRS	Rwy Idg	5197
055°	TDZE	2671
	Apt Elev	2671

NA Circling not authorized NW of Rwy 04-22.
GPS or RNP-0.3 Required.
DME/DME RNP-0.3 NA.



MISSED APPROACH: Climb to 5000
direct TIGAH WP and hold.

AWOS-3 120.0	HCF APPROACH 126.0 278.3	CTAF 122.9
------------------------	------------------------------------	----------------------

Procedure NA for arrivals on UPP VORTAC Airway radials 149 CW 268.
Procedure NA for arrivals at HEFTI on V5 northwest bound.



ELEV 2671



CATEGORY	A	B	C	D
RNAV MDA	3220-1	549 (600-1)	3220-1½ 549 (600-1½)	3220-1¾ 549 (600-1¾)
CIRCLING	3520-1 849 (900-1)	3520-1¼ 849 (900-1¼)	3520-½ 849 (900-½)	3880-3 1209 (1300-3)

MIRL Rwy 4-22
REIL Rwy 4 and 22

RNAV (GPS) RWY 22




KAMUELA/ WAIMEA-KOHALA(MUE)(PHMU)

APP CRS	Rwy Idg	5197
235°	TDZE	2671
	Apt Elev	2671

▽ GPS or RNP-0.3 Required. DME/DME RNP-0.3 NA.
△ NA Circling not authorized NW of Rwy 04-22.
 Straight-in minimums NA at night.

MISSED APPROACH: Climb to 5000
 direct JASON WP and hold.

AWOS-3 120.0	HCF APPROACH 126.0 278.3	CTAF 122.9 0
------------------------	------------------------------------	------------------------






CATEGORY	A	B	C	D
LNAV MDA	3660-1¼ 989 (1000-1¼)	3660-1½ 989 (1000-1½)	3660-3	989 (1000-3)
CIRCLING	3660-1¼ 989 (1000-1¼)	3660-1½ 989 (1000-1½)	3660-3 989 (1000-3)	3880-3 1209 (1300-3)

MIRL Rwy 4-22
 REIL Rwy 4 and 22

VOR/DME MUE 113.3 Chan 80	APP CRS 237°	Rwy Idg TDZE Apt Elev N/A N/A 2671
---	------------------------	--

▼ Circling NA NW of Rwy 4-22. MISSED APPROACH: Climb to 5000 via MUE R-234 to JASON Int/12.5 DME and hold.

AWOS-3 120.0	HCF APPROACH 126.0 278.3	CTAF 122.9
------------------------	------------------------------------	----------------------



		A	B	C	D
Knots	60 90 120 150 180	3680-1¼	3680-1½	3680-3	3880-3
Min:Sec		1009 (1100-1¼)	1009 (1100-1½)	1009 (1100-3)	1209 (1300-3)
CATEGORY		CIRCLING			


VOR/DME RWY 4

KAMUELA/ WAIMEA-KOHALA (MUE) (PHMU)

VOR/DME MUE	APP CRS	Rwy Idg	5197
113.3	054°	TDZE	2671
Chan 80		Apt Elev	2671



⚠ Circling NA NW of Rwy 4-22. MISSED APPROACH: Climb to 5000 via MUE R-057 to TIGAH Int/13.2 DME and hold.

AWOS-3 120.0	HCF APPROACH 126.0 278.3	CTAF 122.9
------------------------	------------------------------------	----------------------



Procedure NA for Arrival at MYNAH via V11 south bound.

ENROUTE FACILITIES




CATEGORY	A		B		C		D		Knots	60	90	120	150	180
	Altitude	Distance	Altitude	Distance	Altitude	Distance	Altitude	Distance						
S-4	3220-1	549 (600-1)	3220-1½	549 (600-1½)	3220-1¾	549 (600-1¾)	3220-2	549 (600-2)						
CIRCLING	3520-1	849 (900-1)	3520-1¼	849 (900-1¼)	3520-2½	849 (900-2½)	3880-3	1209 (1300-3)	Min:Sec					

MIRL Rwy 4-22
REIL Rwy 4 and Rwy 22

AIRPORT DIAGRAM

KAPOLEI/ KALAELOA (JOHN RODGERS FIELD) (JRF)(PHJR)
AL-761 (FAA) KAPOLEI, HAWAII



CAUTION: BE ALERT TO RUNWAY CROSSING CLEARANCES.
READBACK OF ALL RUNWAY HOLDING INSTRUCTIONS IS REQUIRED.

ATIS 119.8
 KALAELOA TOWER ★
 132.6 340.2
 GND CON
 123.8 336.4
 CLNC DEL
 121.7 380.5

PAC. 08 APR 2010 to 03 JUN 2010


NDB RWY 4R

HN LOM 242	APP CRS 037°	Rwy Idg TDZE Apt Elev	8000 17 30
----------------------	------------------------	-----------------------------	---------------------------------------


KAPOLEI/ KALAELOA (JOHN RODGERS FIELD) (JRF)(PHJR)

<p>Circling not authorized north of Rwy 11 and 22R.</p>	<p>MALSF</p>	<p>MISSED APPROACH: Climbing right turn to 2600 via 175° bearing from HN LOM, then climbing right turn to 4900 direct HN LOM and hold.</p>

ATIS 119.8	HCF APPROACH 118.3 269.0	KALAELOA TOWER ★ 132.6(CTAF) 340.2	GND CON 123.8 336.4	CLNC DEL 121.7 380.5
----------------------	------------------------------------	--	-------------------------------	--------------------------------



2600	4900	HN
BRG 175°		
HN LOM		242



CATEGORY	A	B	C	D
S-4R	800-1 783 (800-1)	800-1¼ 783 (800-1¼)	800-2¼ 783 (800-2¼)	800-2½ 783 (800-2½)
CIRCLING	800-1 770 (800-1)	800-1¼ 770 (800-1¼)	800-2¼ 770 (800-2¼)	800-2½ 770 (800-2½)

HIRL Rwy 4R-22L

MIRL Rwy 4L-22R and 11-29


VORTAC HNL 114.8 Chan 95	APP CRS 074°	Rwy Idg TDZE Apt Elev 8000 17 30
--	------------------------	--

VOR/DME RWY 4R


KAPOLEI / KALAELOA (JOHN RODGERS FIELD) (JRF)(PHJR)

MAISF MISSED APPROACH: Climbing right turn to 3000 via heading 248° and HNL VORTAC R-241 to GECKO/HNL 22.37 DME and hold.



ATIS 119.8	HCF APPROACH 118.3 269.0	KALAELOA TOWER ★ 132.6 (CTAF) 340.2	GND CON 123.8 336.4	CLNC DEL 121.7 380.5
----------------------	------------------------------------	--	-------------------------------	--------------------------------



HONOLULU
114.8 HNL
Chan 95



Procedure NA for arrivals at GECKO via V16 southeast bound.




CATEGORY	A	B	C	D
S-4R	560-1 543 (600-1)	560-1½ 543 (600-1½)	560-1¾ 543 (600-1¾)	560-2 543 (600-2)
CIRCLING	560-1 530 (600-1)	620-1 590 (600-1)	620-1½ 590 (600-1½)	620-2 590 (600-2)

HIRL Rwy 4R-22L
 MIRL Rwy 4L-22R and 11-29L


AIRPORT DIAGRAM

AL-759 (FAA)

ATIS
128.2
MOLOKAI TOWER ★
125.7 306.2
GND CON
121.9



21°09.5'N



21°09'N

RWY 5-23
S30, D48
RWY 17-35
S13

**CAUTION: BE ALERT TO RUNWAY CROSSING CLEARANCES.
READBACK OF ALL RUNWAY HOLDING INSTRUCTIONS IS REQUIRED.**

157°06'W

157°05.5'W


PAC: 08 APR 2010 to 03 JUN 2010

BLUSH ONE DEPARTURE

ATIS
128.2
GND CON
121.9
MOLOKAI TOWER ★
125.7 (CTAF) 306.2
HCF APPROACH
124.1 317.5

TAKE-OFF OBSTACLES:

Rwy 5: Pole 2254' from DER, 222' right of centerline, 45' AGL/565' MSL.
Tree 1.12 NM from DER, 720' right of centerline, 50' AGL/675' MSL.
Fenceline beginning 147' from DER, 177' left of centerline, up to 12' AGL/471' MSL.
Multiple trees and bushes beginning 50' from DER, 273' left of centerline, up to 50' AGL/551' MSL.
Obstruction light 1366' from DER, 79' right of centerline, 30' AGL/528' MSL.
Multiple poles beginning 3065' from DER, 644' left of centerline, up to 45' AGL/623' MSL.
Multiple trees beginning 4155' from DER, 184' right of centerline, up to 50' AGL/714' MSL.



TAKE-OFF MINIMUMS:

Rwy 17, 35, 23: NA, ATC.

Rwy 5: STANDARD with minimum obstacle climb of 395' per NM to 1600'.

NOTE: Chart not to scale.




DEPARTURE ROUTE DESCRIPTION

TAKE-OFF RUNWAY 5: Climb via 049° heading to 860, then climbing left turn to 5000 via 034° heading and CKH R-075 to BLUSH INT.

HAPAI TWO DEPARTURE

ATIS
128.2
GND CON
121.9
MOLOKAI TOWER ★
125.7 (CTAF) 306.2
HCF APPROACH
124.1 317.5

TAKE-OFF MINIMUMS:

Rwy 17, 35, 23: NA, ATC.

Rwy 5: STANDARD with minimum obstacle climb of 395' per NM to 1600'.

NOTE: DME Required.

TAKE-OFF OBSTACLES:

Rwy 5: Pole 2254' from DER, 222' right of centerline, 45' AGL/565' MSL.

Tree 1.12 NM from DER, 720' right of centerline, 50' AGL/675' MSL.

Fenceline beginning 147' from DER, 177' left of centerline, up to 12' AGL/471' MSL.

Multiple trees and bushes beginning 50' from DER, 273' left of centerline, up to 50' AGL/551' MSL.

Obstruction light 1366' from DER, 79' right of centerline, 30' AGL/528' MSL.

Multiple poles beginning 3065' from DER, 644' left of centerline, up to 45' AGL/623' MSL.

Multiple trees beginning 4155' from DER, 184' right of centerline, up to 50' AGL/714' MSL.

NOTE: Chart not to scale

DEPARTURE ROUTE DESCRIPTION

TAKE-OFF RUNWAY 5: Climbing left turn via 360° heading and MKK VORTAC R-030 to HAPAI/10 DME. Thence. . . .

. . . . via (Transition). Maintain 4,000.

LOKIE TRANSITION (HAPAI2.LOKIE): From over HAPAI via MKK VORTAC 10 DME Arc CCW to LOKIE.MOLOKAI TRANSITION (HAPAI2.MKK): From over HAPAI via 210° heading and MKK R-030 to MKK VORTAC.

RNAV (GPS)-B





KAUNAKAKAI/MOLOKAI (MKK) (PHMK)

APP CRS 043°	Rwy Idg TDZE Apt Elev	N/A N/A 454
------------------------	-----------------------------	--

NA GPS or RNP-0.3 Required.
DME/DME RNP-0.3 NA.

MISSED APPROACH: Climb to 1400 then climbing left turn to 5000 direct MKK VORTAC and hold.

ATIS 128.2	HCF APPROACH 124.1 317.5	MOLOKAI TOWER ★ 125.7 (CTAF) 306.2	GND CON 121.9
----------------------	------------------------------------	--	-------------------------



CATEGORY	A	B	C	D
CIRCLING	980-1 526 (600-1)		1080-1¾ 626 (700-1¾)	1460-3 1006 (1100-3)



REIL Rwy 5
MIRL Rws 5-23 and 17-35

VOR or TACAN or GPS-A KAUNAKAKAI/MOLOKAI (MKK) (PHMK)



VORTAC MKK 116.1 Chan 108	APP CRS 070°	Rwy Idg TDZE Apt Elev N/A N/A 454
---	------------------------	---

MISSED APPROACH: Climbing left turn via heading 360° to join the MKK R-030 northeast to 3500. Then left turn direct MKK VORTAC and hold.

ATIS 128.2	HCF APPROACH 124.1 317.5	MOLOKAI TOWER ★ 125.7 (CTAF) 306.2	GND CON 121.9
----------------------	------------------------------------	--	-------------------------



ELEV 454



CATEGORY	A	B	C	D
CIRCLING	1800-1¼ 1346 (1400-1¼)	1800-1½ 1346 (1400-1½)	1800-3	1346 (1400-3)
DME MINIMUMS				
CIRCLING	1040-1	586 (600-1)	1080-1¾ 626 (700-1¾)	1460-3 1006 (1100-3)

REIL Rwy 5 ①
MIRL Rwys 5-23 and 17-35 ①
FAF to MAP 3.8 NM


Knots	60	90	120	150	180
Min:Sec	3:48	2:32	1:54	1:31	1:16

LOC/DME I-LNY 111.1 Chan 48	APP CRS 033°	Rwy Idg TDZE Apt Elev	5001 1305 1308
---	------------------------	-----------------------------	---



When local altimeter setting not received, procedure not authorized, except for operators with approved weather reporting service.
 Glide slope unusable for coupled approaches below 1505 MSL.
 Glide slope unusable beyond 5 degrees left of course.

MISSED APPROACH: Climb to 1700 then climbing left turn to 3000 via LNY R-278 to GRAMY Int/LNY 10 DME and hold.

ASOS 118.375	HCF APPROACH 119.3 307.1	CTAF 122.9 0
------------------------	------------------------------------	------------------------



ELEV 1308	
-----------	--



CATEGORY	A	B	C	D
S-ILS 3	1505-¾ 200 (200-¾)			
S-LOC 3	1580-1 275 (300-1)			
CIRCLING	1840-1 532 (600-1)	1880-1 572 (600-1)	1900-1½ 592 (600-1½)	1900-2 592 (600-2)

FAF to MAP 3.4 NM					
Knots	60	90	120	150	180
Min:Sec	3:24	2:16	1:42	1:21	1:08



RNAV (GPS) RWY 3

LANAI CITY / LANAI (LNY)(PHNY)

APP CRS	Rwy Idg	5001
033°	TDZE	1305
	Apt Elev	1308

DME/DME RNP-0.3 NA. MISSED APPROACH: Climbing left turn to 3300 direct GRAMY and hold.

ASOS 118.375	HCF APPROACH 119.3 307.1	CTAF 122.9
------------------------	------------------------------------	----------------------



CATEGORY	A		B		C		D	
	1720-1	415 (500-1)	1720-1¼	415 (500-1¼)				
LNVA MDA	1720-1		415 (500-1)		1720-1¼		415 (500-1¼)	
CIRCLING	1840-1 532 (600-1)	1880-1 572 (600-1)	1900-1½ 592 (600-1½)	1900-2 592 (600-2)				

ELEV	1308
------	------

PAC. 08 APR 2010 TO 03 JUN 2010

MIRL Rwy 3-21





VOR or TACAN or GPS-A LANAI CITY/LANAI (LNY)(PHNY)

VORTAC LNY 117.7 Chan 124	APP CRS 098°	Rwy Idg TDZE Apt Elev N/A N/A 1308
---	------------------------	--

⚠ When local altimeter not received, procedure not authorized, except for operators with approved weather reporting service.

MISSED APPROACH: Climbing right turn to 2000 via LNY R-278 to GRAMY Int/LNY 10 DME and hold.

ASOS 118.375	HCF APPROACH 119.3 307.1	CTAF 122.9
------------------------	------------------------------------	----------------------



CATEGORY	A	B	C	D	Knots	60	90	120	150	180
CIRCLING	1840-1½ 532 (600-1½)	1880-1½ 572 (600-1½)	1900-1½ 592 (600-1½)	1900-2 592 (600-2)	Min:Sec					




VOR or TACAN RWY 3

LANAI CITY / LANAI (LNY)(PHNY)

VORTAC LNY 117.7 Chan 124	APP CRS 025°	Rwy Idg TDZE Apt Elev 5001 1305 1308
---	------------------------	--

MISSED APPROACH: Climb to 1720 then climbing left turn to 3300 via heading 240° and LNY VORTAC R-278 to GRAMY Int/LNY 10 DME and hold.

ASOS 118.375	HCF APPROACH 119.3 307.1	CTAF 122.9 0
------------------------	------------------------------------	------------------------



CATEGORY	A	B	C	D
S-3	1660-1 355 (400-1)			1660-1¼ 355 (400-1¼)
CIRCLING	1840-1 532 (600-1)	1880-1 572 (600-1)	1900-1½ 592 (600-1½)	1900-2 592 (600-2)

Knots					
60	90	120	150	180	
Min:Sec					
1:12	0:48	0:36	0:29	0:24	

PAC. 08 APR 2010 to 03 JUN 2010


AIRPORT DIAGRAM

AL-776 (FAA)

LIHUE (LIH)(PHLI)
LIHUE, HAWAII

ATIS
127.2
LIHUE TOWER ★
118.9 263.1
GND CON
121.9

CAUTION: BE ALERT TO RUNWAY CROSSING CLEARANCES.
READBCK OF ALL RUNWAY HOLDING INSTRUCTIONS IS REQUIRED.




RWY 3-21
S75, D200, DT350, TT440, SBTT550, DDT730
RWY 17-35
S75, D175, DT250, TT340, SBTT430, DDT630

PAC: 08 APR 2010 to 03 JUN 2010

DIANE ONE DEPARTURE

ATIS
127.2
GND CON
121.9
LIHUE TOWER★
118.9 (CTAF) 263.1
HCF APPROACH
126.5 269.4



TAKE-OFF MINIMUMS: Rwy 21, 2400-3

NOTE: Honolulu CERAP radio call is "Honolulu Center".

NOTE: Ridgeline 1.5 NM south to 6 NM southwest, 900' to 2400' MSL.

NOTE: Terrain heights to 2297' MSL occur within 4.2 NM southwest of the airport.

NOTE: This Departure not authorized for Rwy 3, Rwy 17, Rwy 35.

NOTE: Chart not to scale.



DEPARTURE ROUTE DESCRIPTION

TAKE-OFF RUNWAY 21:

To V15: Climb runway heading to 550 then climbing left turn, heading 090°, to intercept LIH R-110 (V15), maintain 5000, direct BOOKE INT or as assigned.

To LIH R-148: Climb runway heading to 550, then climbing left turn, heading 120°, to intercept LIH R-148, maintain 3000, direct NAPUA INT or as assigned.




ILS or LOC RWY 35

LIHUE (LIH)(PHL)

LOC/DME I-LIH 110.9 Chan 46	APP CRS 349°	Rwy ldg TDZE Apt Elev	6500 96 153
--	------------------------	-----------------------------	--

MALSR MISSED APPROACH: Climb to 600 then climbing right turn to 3000 via LIH R-070. DME aircraft continue to KREEN/LIH 12 DME and hold. Non-DME aircraft continue climb to 4000 then right turn direct LIH VORTAC and hold East, left turn, 250° inbound.


ATIS 127.2	HCF APPROACH 126.5 269.4	LIHUE TOWER ★ 118.9 (CTAF) 263.1	GND CON 121.9
----------------------	------------------------------------	--	-------------------------



FAF to MAP 5.4 NM		CATEGORY				
		A	B	C	D	E
		S-ILS 35 296-1/2 200 (200-1/2)				
		S-LOC 35 400-1/2 304 (300-1/2) 400-3/4 304 (300-3/4)				
		520-1	620-1	620-1 1/2	720-2	
		367 (400-1)	467 (500-1)	467 (500-1 1/2)	567 (600-2)	NA
CIRCLING						
Knots	60 90 120 150 180					
Min:Sec	5:24 3:36 2:42 2:10 1:48					

LIHUE FIVE DEPARTURE

ATIS
 127.2
 GND CON
 121.9
 LIHUE TOWER★
 118.9 (CTAF) 263.1
 HCF APPROACH
 126.5 269.4



NOTE: DME Required.

NOTE: Honolulu CERAP radio call is "Honolulu Center".

NOTE: Chart not to scale.




DEPARTURE ROUTE DESCRIPTION

TAKE-OFF RUNWAYS 3 and 35: Climb runway heading to 500, then climbing right turn to heading 080°, expect radar vectors to intercept LIH R-110 to BOOKE DME fix. MEA 5000.

LOST COMMUNICATIONS: If not in contact with Honolulu CERAP one minute after departure, maintain SID heading until 10 NM east of LIH VORTAC, then intercept LIH R-110 to BOOKE DME fix. MEA 5000.

RICHE TWO DEPARTURE

ATIS
127.2
GND CON
121.9
LIHUE TOWER★
118.9 (CTAF) 263.1
HCF APPROACH
126.5 269.4



NOTE: DME Required.

NOTE: Honolulu CERAP radio call is "Honolulu Center".

NOTE: Terrain heights to 2297' occur within 4.5 NM southwest of the airport.

NOTE: Chart not to scale.



DEPARTURE ROUTE DESCRIPTION

TAKE-OFF RUNWAY 17: Climb runway heading to 500 feet, then climbing left turn to heading 150°, expect radar vectors to intercept LIH R-110 to BOOKE DME fix. MEA 5000.

TAKE-OFF RUNWAY 21: Immediate climbing left turn to heading 120 until crossing LIH R-150, thence fly heading 150°, expect radar vectors to intercept LIH R-110 to BOOKE DME fix. MEA 5000.

LOST COMMUNICATIONS: If not in contact with Honolulu CERAP one minute after departure, maintain SID heading until 10 NM southeast of LIH VORTAC, then intercept LIH R-110 to BOOKE DME fix. MEA 5000.

RNAV (GPS) RWY 17

LIHUE (LIH)(PHLI)

APP CRS	Rwy Idg	6500
184°	TDZE	99
	Apt Elev	153

▼ Circling NA between Rwys 3 and 35.
▲ DME/DME RNP-0.3 NA.
 Circling NA at night.




MISSED APPROACH: Climbing left turn to 3000 direct NAGAI and hold.

ATIS
127.2

HCF APPROACH
126.5 269.4

LIHUE TOWER★
118.9(CTAF) 263.1

GND CON
121.9



CATEGORY	A	B	C	D
LNNAV MDA	740-1	641 (600-1)	740-1¾ 641 (600-1¾)	740-2 641 (600-2)
CIRCLING	740-1 587 (600-1)	1000-1¼ 847 (900-1¼)	1060-2¾ 907 (1000-2¾)	1060-3 907 (1000-3)

RNAV (GPS) Y RWY 21

LIHUE (LIH)(PHLI)

APP CRS	Rwy ldg	6295
214°	TDZE	118
	Apt Elev	153

▼ DME/DME RNP-0.3 NA.
▲ Circling NA between Rwy 3 and 35.
 Circling NA at night.


MISSED APPROACH: Climbing left turn to 3000 direct NAGAI and hold.

ATIS
127.2


HCF APPROACH
126.5 269.4

LIHUE TOWER ★
118.9(CTAF) **0 263.1**


GND CON
121.9




ELEV 153 Rwy 21 ldg 6295'



HIRL Rwy 17-35 **Ⓛ**
 REIL Rwy 3, 17 and 21 **Ⓛ**
 MIRL Rwy 3-21 **Ⓛ**



CATEGORY	A	B	C	D
LNNAV MDA	580-1¼ 462 (500-1¼)			580-1½ 462 (500-1½)
CIRCLING	600-1¼ 447 (500-1¼)	1000-1¼ 847 (900-1¼)	1060-2¾ 907 (1000-2¾)	1060-3 907 (1000-3)



RNAV (GPS) Y RWY 35


LIHUE (LIH)(PHLI)

APP CRS	Rwy Idg	6500
349°	TDZE	96
	Apt Elev	153



⚠ For inoperative MALS, increase LNAV Cat. A visibility to 1 mile and Cat. E to 3 miles. Circling NA west of Rwy 17-35.
⚠ Circling NA at night. DME/DME RNP-0.3 NA.

MALS
 MALS
MISSED APPROACH: Climbing right turn to 3000 direct KREEN WP and hold.

ATIS 127.2	HCF APPROACH 126.5 269.4	LIHUE TOWER* 118.9 (CTAF) 263.1	GND CON 121.9
-----------------------------	---	--	--------------------------------



ELEV 153	Rwy 21 Idg 6295'
----------	------------------



CATEGORY	A	B	C	D	E
LNNAV MDA	920- ³ / ₄ 824 (800- ³ / ₄)		920-2 824 (800-2)	920-2 ¹ / ₄ 824 (800-2 ¹ / ₄)	920-2 ¹ / ₂ 824 (800-2 ¹ / ₂)
CIRCLING	920-1 767 (800-1)	920-1 ¹ / ₄ 767 (800-1 ¹ / ₄)	920-2 ¹ / ₄ 767 (800-2 ¹ / ₄)	920-2 ¹ / ₂ 767 (800-2 ¹ / ₂)	NA

RNAV (RNP) Z RWY 21



LIHUE (LIH)(PHLI)

APP CRS	Rwy Idg	6295'
214°	TDZE	118
	Apt Elev	153


NA *Missed approach requires minimum climb rate of 350 feet per NM to 2500. For uncompensated Baro-VNAV systems, procedure NA below 14° C (57°F) or above 48° C (119°F). GPS REQUIRED.

MISSED APPROACH: Climbing left turn to 3000 direct OLOYI and hold.

ATIS 127.2	HCF APPROACH 126.5 269.4	LIHUE TOWER* 118.9(CTAF) 263.1	GND CON 121.9
-----------------------------	---	---	--------------------------------



Procedure NA for arrivals at GRAIL via V16 southeast bound and at OLOYI via V15 southeast bound.



CATEGORY	A	B	C	D
RNP 0.30 DA *	663-2 545 (600-2)			
RNP 0.30 DA	1078-4 960 (1000-4)			

HIRL Rwy 17-35
REIL Rwys 3, 17 and 21
MIRL Rwy 3-21

SPECIAL AIRCRAFT & AIRCREW AUTHORIZATION REQUIRED

RNAV (RNP) Z RWY 35

LIHUE (LIH)(PHLI)


APP CRS	Rwy ldg	6500
349°	TDZE	96
	Apt Elev	153

T GPS REQUIRED. For inoperative MALS, increase RNP 0.30 visibility to 1¾. For uncompensated Baro-VNAV systems, procedure NA below 14°C (57°F) or above 48°C (119°F).



MALS


MISSED APPROACH: Climbing right turn to 3000 direct KREEN and hold.

ATIS 127.2	HCF APPROACH 126.5 269.4	LIHUE TOWER* 118.9 (CTAF) 0 263.1	GND CON 121.9
----------------------	------------------------------------	---	-------------------------



ELEV 153 Rwy 21 ldg 6295'



CATEGORY	A	B	C	D
RNP 0.30 DA	599-1¼ 503 (500-1¼)			



SPECIAL AIRCRAFT & AIRCREW AUTHORIZATION REQUIRED

VORTAC LIH	APP CRS	Rwy Idg	N/A
113.5	300°	TDZE	N/A
Chan 82		Apt Elev	153



▼ Circling NA west of Rwy 17-35.
Procedure NA at night.

MISSED APPROACH: Climbing right turn to 3000 via heading 100° and LIH VORTAC R-070 then climbing right turn to 4000 direct LIH VORTAC and hold.

ATIS 127.2	HCF APPROACH 126.5 269.4	LIHUE TOWER★ 118.9(CTAF) 263.1	GND CON 121.9
----------------------	------------------------------------	--	-------------------------



ELEV 153 | Rwy 21 Idg 6295'



Knots	60	90	120	150	180	
	Min:Sec					
CATEGORY	A		B		C	D
CIRCLING	800-1 647 (700-1)		800-1¾ 647 (700-1¾)		800-2 647 (700-2)	

VOR/DME or TACAN RWY 21

LIHUE (LIH)(PHL)

VORTAC LIH 113.5 Chan 82	APP CRS 191°	Rwy ldg TDZE Apt Elev 6295 118 153
--	------------------------	--



Circling NA west of Rwy 17-35.
Circling NA at night.





MISSED APPROACH: Climbing left turn to 3000 via heading 152° and LIH VORTAC R-148 to NAGAI/12 DME and hold.

ATIS
127.2

HCF APPROACH
126.5 269.4

LIHUE TOWER ★
118.9 (CTAF) 0 263.1

GND CON
121.9



Knots	60	90	120	150	180
Min:Sec					


CATEGORY	A	B	C	D
S-21	520-1	402 (400-1)	520-1¼	402 (400-1¼)
CIRCLING	520-1 367 (400-1)	620-1 467 (500-1)	620-1½ 467 (500-1½)	720-2 567 (600-2)

VOR or TACAN RWY 35

LIHUE (LIH)(PHL)


VORTAC LIH	APP CRS	Rwy Idg	6500
113.5	328°	TDZE	96
Chan 82		Apt Elev	153

▼ Circling NA at night. DME or RADAR REQUIRED
 Inoperative table does not apply.
 Circling NA west of Rwy 17-35.


MALSR 

MISSED APPROACH: Climbing right turn to 3000 via heading 100° and LIH VORTAC R-070 to KREEN/RADAR and hold.



ATIS 127.2	HONOLULU CENTER 126.5 269.4	LIHUE TOWER ★ 118.9 (CTAF) 263.1	GND CON 121.9
----------------------	---------------------------------------	---	-------------------------



SOUTH KAUAI
115.4 SOK
Chan 101



ELEV 153 | Rwy 21 Idg 6295'



CATEGORY	A	B	C	D	E
S-35	600-1	504 (500-1)	600-1½	504 (500-1½)	600-1¾ 504 (500-1¾)
CIRCLING	600-1 447 (500-1)	620-1 467 (500-1)	620-1½ 467 (500-1½)	720-2	567 (600-2)

Knots	60	90	120	150	180
Min:Sec					